

# MHW-S380R7-HC Management Server

[www.boschsecurity.com](http://www.boschsecurity.com)



**BOSCH**

Invented for life



- ▶ Highest performance with two quad-core Intel® Xeon® Processors E5606 (2.13 GHz, 8 MB L3 cache, 80 W, DDR3-1066)
- ▶ 8 GB (2 x 4 GB) PC3-10600R (running at 1066 MHz) Registered DIMMs (RDIMMs)
- ▶ 6 Gigabit Ethernet Ports: 2 x HP NC382i Dual Port Multifunction Gigabit Server Adapters and 1 x NC382T PCIe Dual Port Gigabit Server Adapter
- ▶ 2U rack for 19" rack deployment
- ▶ Protected by HP Services

The HP ProLiant DL380 Generation 7 (G7) continues to deliver on its history of engineering excellence and delivers superior performance with improved consolidation over previous-generation servers. Increased flexibility, enterprise-class uptime, advanced management features, latest processor series, and 2U density make it well-suited for demanding video applications.

The MHW-S380R7-HC Management Server is designed for highest-performance video applications that require high availability and redundancy. With its hot plug fans and power supplies, it delivers high system availability where the number of unplanned downtimes due to hardware failures is minimized, while its RAID controller provides internal RAID-1 operating system protection.

With two state-of-the-art quad-core Intel® Xeon® Processors E5606 (2.13 GHz, 8 MB L3 cache, 80 W, DDR3-1066), and 8 GB (2 x 4 GB) PC3-10600R (running at 1066 MHz) Registered DIMMs, it provides the performance, scalability, and support for memory-demanding applications in large-sized environments. In addition, HP Services protects the server with a 4-hour 24 x 7, 3-year advanced warranty in selected countries.

The server comes in a 2U, 19" rack mount version with a quick-deploy rail system, including sliding universal rails. The rack mount version allows access to all system components for easy in-rack serviceability.

## Functions

The MHW-S380R7-HC Management Server provides the performance and memory needed for large-sized environments and is the high-end product in the Bosch server portfolio for enterprise environments.

## Certifications and Approvals

Region	Certification	
Europe	CE	DL380 G7 Server
Global	RoHS	HP Compliance with RoHS directives

## Installation/Configuration Notes

The MHW-S380R7-HC Management Server is ideal for performance- and memory-demanding enterprise environments. Please refer to the respective application data sheets to get detailed information.

**Notice**

This Management Server comes in three standard localizations:  
 MHW-S380R7-HCDE German Localization/  
 Keyboard  
 MHW-S380R7-HCUK British English Localization/  
 Keyboard  
 MHW-S380R7-HCUS American English  
 Localization/Keyboard  
 Additional optional keyboards listed under  
**Ordering Information** are available.

**Parts Included**

Quantity	Components
1	HP DL380 G7 CTO Chassis
2	• HP E5606 DL380 G7 Processor
2	• HP 4 GB 2Rx8 PC3-10600R-9 Memory
1	• HP Slim 12.7 mm SATA DVD Optical
2	• HP 146 GB 3 G SAS 15 K 2.5 in DP ENT HDD
1	• HP NC382T PCIe Dual Port Gigabit Svr Adapter
2	• HP 460 W HE 12 V Hotplug AC Power Supply
1	• HP RAID-1
1	MS Windows Server 2008 R2 Standard Edition, 64 bit
1	HP HW Support, 4-hour 24 x 7, 3-year advanced warranty (not available in all countries, registration required)

**Technical Specifications**

Electrical	
Input requirements (per 460 W power supply)	
• rated line voltage	100 to 120 VAC, 200 to 240 VAC
• rated input current	5.5 A (at 100 VAC)
	2.6 A (at 200 VAC)
• rated input frequency	50 to 60 Hz
• rated input power	526 W (at 100 VAC)
	505 W (at 200 VAC)
BTU rating	1794 BTU/h (at 100 VAC)
	1725 BTU/h (at 200 VAC)
Output power (per power supply)	
• rated steady-state power	460 W (at 100 to 120 VAC)

	460 W (at 200 to 240 VAC)
• maximum peak power	460 W (at 100 to 120 VAC)
	460 W (at 200 to 240 VAC)
Mechanical	
Dimensions (H x W x D)	8.59 x 44.54 x 69.22 cm (3.38 x 17.54 x 27.25 in)
Environmental	
System inlet temperature	
• operating	10 °C to 35 °C (50 °F to 95 °F) at sea level with an altitude derating of 1.0 °C per every 305 m (1.8 °F per every 1000 ft) above sea level to a maximum of 3050 m (10,000 ft), no direct sustained sunlight. Maximum rate of change is 10 °C/h (18 °F/h). The upper limit may be limited by the type and number of options installed.
	System performance may be reduced if operating with a fan fault or above 30 °C (86 °F).
• non-operating	-30 °C to 60 °C (-22 °F to 140 °F). Maximum rate of change is 20 °C/h (36 °F/h).
Relative humidity	
• operating	10 to 90% relative humidity (Rh), 28 °C (82.4 °F) maximum wet bulb temperature, non-condensing
• non-operating	5 to 95% relative humidity (Rh), 38.7 °C (101.7 °F) maximum wet bulb temperature, non-condensing

**Notes:**

- General technical specifications for the server are provided in the HP DL380 G7 QuickSpecs (Worldwide – Version 14 – August 18, 2010).
- Configuration specifications are supplied in the Parts Included section.

Hewlett Packard and the HP logo are registered trademarks of Hewlett Packard, all rights reserved. All data and dimensions are referenced from the Hewlett Packard QuickSpecs and are subject to change without notice.

Intel and Xeon are trademarks of Intel Corporation in the U.S. and other countries.

**Ordering Information****MHW-S380R7-HCDE Bosch VMS Central Server High-end (DE)**

High performance high-end server, German localization included

Order number **MHW-S380R7-HCDE**

**MHW-S380R7-HCUK Bosch VMS Central Server High-end (UK)**

High performance high-end server, British English localization included

Order number **MHW-S380R7-HCUK**

### **MHW-S380R7-HCUS Bosch VMS Central Server High-end (US)**

High performance high-end server, American English localization included

Order number **MHW-S380R7-HCUS**

---

#### **Accessories**

##### **MHW-AWLCK-DE**

Localization (Keyboard): Germany—German

Order number **MHW-AWLCK-DE**

---

##### **MHW-AWLCK-FR**

Localization (Keyboard): France—French

Order number **MHW-AWLCK-FR**

---

##### **MHW-AWLCK-IT**

Localization (Keyboard): Italy—Italian

Order number **MHW-AWLCK-IT**

---

##### **MHW-AWLCK-UK**

Localization (Keyboard): United Kingdom—British English

Order number **MHW-AWLCK-UK**

---

##### **MHW-AS1P-SCSI 1-Chan. U320 PCI-E SCSI HBA**

1-Chan. U320 PCI-E SCSI HBA

Order number **MHW-AS1P-SCSI**

---

##### **MHW-ASILO-ADP ILO Advanced Pack ALL**

Integrated Lights Out remote management package

Order number **MHW-ASILO-ADP**

---

#### **Represented by:**

##### **Americas:**

Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

##### **Europe, Middle East, Africa:**

Bosch Security Systems B.V.  
P.O. Box 80002  
5617 BA Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

##### **Asia-Pacific:**

Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia

##### **China:**

Bosch (Shanghai) Security Systems Ltd.  
201 Building, No. 333 Fuquan Road  
North IBP  
Changning District, Shanghai  
200335 China  
Phone: +86 21 22181111  
Fax: +86 21 22182398  
www.boschsecurity.com.cn

##### **America Latina:**

Robert Bosch Ltda Security Systems Division  
Via Anhanguera, Km 98  
CEP 13065-900  
Campinas, Sao Paulo, Brazil  
Phone: +55 19 2103 2860  
Fax: +55 19 2103 2862  
al.securitysystems@bosch.com  
www.boschsecurity.com