

MIC Series 400 Public Address Camera

www.boschsecurity.com



BOSCH

Invented for life



- ▶ Built-in speakers
- ▶ Brushless motor technology
- ▶ Host of mounting and viewing options
- ▶ Integrated long-life silicone wiper
- ▶ Multi-protocol operation

The MIC Series 400 public address camera has been designed to offer an extremely reliable, robust, and high quality surveillance solution for security applications that demand the very best performance. Precision engineered to exacting standards, the range offers numerous benefits over the use of traditional dome and PTZ cameras, and comes with a variety of options in order to offer a best fit solution for virtually any application that requires video and voice communication.

The MIC Series 400 public address camera affords the user directional one-way voice communication thanks to its 100 dB built-in twin speaker system. Coupled with leading PTZ camera technology, the range is suitable for a host of crowd control and public space applications.

Rated to an industry leading IP68 (speakers rated to IP67), the compact, vandal-resistant, machined aluminum camera housing is suitable for installation in the harshest of environments. Machined from solid aluminum, the MIC Series 400 cameras ensure corrosion protection by using two different processes; first an Alocrom 1200 coating, then a robust powder paint coating. Alocrom 1200 is a chromate conversion coating of aluminum, used in the aerospace and defense industries where a protective layer is required

to improve corrosion resistance. The optically-perfect flat viewing window and integrated, long-life silicone wiper ensure razor sharp images are captured in even the most demanding conditions.

The brushless motor technology offers ultra-reliable, whisper-quiet operation with full 360° continuous rotation pan and 196° tilt control for exceptional viewing capability. Small-increment pan/tilt speeds, from just 0.2° per second to 90° per second, give the user precise control. This speed control is especially important when used with video analytic systems, particularly for tracking subjects when fully zoomed in. A choice of true day/night camera modules, offering up to 36x optical zoom (12x digital) are available, providing either 470 TVL NTSC/PAL typical (18x module) or 530 TVL NTSC/PAL typical (36x module). When coupled with upright or inverted mounting capability, the MIC Series 400 public address camera allows the perfect field of view to be achieved every time.

Functions

Built-in speakers

Twin 100 dB speakers offer directional voice communication in addition to the units' flexible surveillance capability.

Note: Requires suitable third party amplifier and microphone.

Brushless motor technology

Whisper-quiet operation and smooth control is provided through the use of ultra-reliable brushless motors.

Host of mounting and viewing options

Faultless operation either upright or inverted gives the user a host of mounting and viewing possibilities.

Integrated wiper

Hot or cold, rain or shine - regardless of the weather the MIC Series 400 public address camera is able to capture the highest possible quality image all year round thanks to its integrated long-life silicone wiper.

Multi-protocol operation

Compatible with virtually any control equipment available today, the MIC Series 400 public address camera is able to seamlessly integrate with the vast majority of security systems

Applications:

- Town Centers
- Railway Stations
- Events
- Crowd Control
- Rapid Deployment
- Stadia
- Remote Locations
- Airports

Certifications and approvals

Electromagnetic Compatibility (EMC)	Complies with FCC Part 15, ICES-003, and CE regulations, including EN50130-4, EN61000-3-2:2006, EN61000-3-3:1995, and EN55022:2006 inc AL:2007
Safety	Complies with CE regulations, UL, EN, and IEC Standards 60950-1 & 22
Weatherproofing	IP68 camera housing, IP67 speakers

Region	Certification	
Europe	CE	AC08-10-Q012 EMC Directive, Low Voltage Directive
USA	UL	AC08-10-Q013 UL 60950-1 2nd Edition: 2007
	FCC	AC08-10-Q013 CFR 47 FCC part 15:2009, Class B
Canada	CSA	AC08-10-Q012 CAN/CSA-C22.2 No. 60950-1-07

Technical specifications

Camera Module

Image sensor	1/4-inch EXview CCD, WDR (36x only)
Horizontal resolution	18x module, 470 TVL NTSC/PAL typical

	36x module, 530 TVL NTSC/PAL typical
Filter	Automatic mechanical IR cut filter
Focus system	Auto or manual
Iris	Auto or manual with slow shutter integration modes
Synchronization	Internal / External (V-Lock)
Signal/Noise ratio	50 dB or more
Back Light Compensation (BLC)	On/Off
White balance	Automatic
Automatic Gain Control (AGC)	-3 to -28 dB, 2 dB steps
Aperture control	16 Steps

18x Optical Zoom Module

Lens	F=4.1 mm (wide) to 73.8 mm (tele), F1.4 to F3.0
Zoom	18x optical (12x digital)
Angle of view	48° (wide) to 2.8° (tele)
Minimum illumination	0.7 lux (F1.4, 1/60s NTSC, 1/50s PAL) 0.11 lux (F1.4, 1/4s NTSC, 1/3s PAL) 0.01 lux (F1.4, 1/4s NTSC, 1/3s PAL ICR on)
Shutter speed	1/1 to 1/10,000 s (22 steps) NTSC, PAL

36x Optical Zoom Module

Lens	F=3.4 mm (wide) to 122.4 mm (tele), F1.6 to F4.5
Zoom	36x optical (12x digital)
Angle of view	57.8° (wide) to 1.7° (tele)
Minimum illumination	1.4 lux (1/60 s NTSC, 1/50 s PAL, typical, F1.6, 50IRE) 0.1 lux (1/4 s NTSC, 1/3 s PAL, typical, F1.6, 50IRE) ICR-ON mode: 0.01 lux (1/4 s NTSC, 1/3 s PAL)
Shutter speed	1/4 to 1/10,000 s (20 steps) NTSC, 1/3 to 1/10,000 s (20 steps) PAL

Twin Speakers

Output	6 W / 8 ohm
Construction	Polyamide UL94 V0
Weatherproofing	IP67
Control	Third party amplifier and microphone

Operational

Auto flip	Yes
Manual flip	Yes

Dynamic privacy zones	Standard, 3D privacy masking with infinite zones
Presets	64 telemetry presets utilizing resolver technology (using FV protocol, 10 camera set-up presets to allow ANPR, color correction etc.)
Preset tours	6 tours each with up to 32 presets
Sector titles	Yes (64 sectors) 20 characters per title
Preset titles	20 character caption for each of the 64 presets
Home position	Yes (preset 1 or tour)

Communication and Protocols

Communication	RS485 / RS422
Control protocol	Bosch or FV protocol cameras available; additional protocols supported are Pelco D, Kalatel, 360 Vision, American Dynamics, Panasonic, Molynx, VCL, and Vicon. These can be loaded using the MIC-USB485CVTR signal converter and Cam-set via a PC. Biphase control requires a Biphase to RS485 converter (MIC-BP4, available separately) installed in the MIC Series PSU to connect to Biphase equipment.

Connectivity

Video	Co-axial via composite cable
Telemetry	Twisted pair. Simplex, half and full duplex operation via composite cable
MIC Universal Camera Setup Software Utility (Cam-set)	Supplied with each camera, Cam-set allows direct connection to a USB equipped PC via the MIC Series PSU or over a full duplex or IP network to provide access to all camera functions and useful diagnostic tools
USB to RS485 signal converter	Allows MIC Series cameras to connect to a PC (supplied free with MIC Series 400 public address camera or available separately)
Power	Via composite cable

Alarms

Alarm inputs	1 tamper input (additional inputs possible with optional alarm card in PSU)
Alarm communication	Tamper switch (ground connection)

Mechanical

Drive unit	Brushless, integral pan/tilt motor drive
Pan angle	360° continuous rotation
Pan speed	Up to 90° per second (variable)
Tilt angle	196°
Tilt speed	0.2° to 90° per second (variable)

Speed control	Closed loop electronics
Preset accuracy	Better than 0.08°
Proportional Pan/Tilt to Zoom	Yes

Construction

Construction material	Machined aluminum
Viewing window	Tempered flat glass
Window wiper	Standard, long-life silicone wiper
Standard color	Black (RAL9005) or Grey (RAL7001)
Standard finish	Alochrom 1200 surface treatment with powder coat paint.
Dimensions (W x H x D)	205 x 420 x 165 mm (8.07 x 16.54 x 6.50 in.) (upright and inverted)
Weight	6.5 Kg (14.33 lb) including 4-in. pitch circle diameter (PCD) base
Configurations available	Upright mount or upright canted at 45° mount. (Inverted mount is possible using software setting and upright camera.)

Environmental

Operational temperature	-20°C to +50°C (-4 °F to 122 °F)
Weatherproofing	IP68 for Camera, IP67 for Speakers

Electrical

Input voltage	18 VAC
Power consumption	25.2 W max

Ordering information

MIC400PABUW14518P MIC Series 400 public address
Public address, 18X, PAL, PTZ camera, Black, Upright, FV Protocol with integrated wiper and privacy function
Order number **MIC400PABUW14518P**

MIC400PABUW14536P MIC Series 400 public address
Public address, 36X, PAL, PTZ camera, Black, Upright, FV Protocol with integrated wiper and privacy function
Order number **MIC400PABUW14536P**

MIC400PAGUW14518P MIC Series 400 public address
Public address, 18X, PAL, PTZ camera, Grey, Upright, FV Protocol with integrated wiper and privacy function
Order number **MIC400PAGUW14518P**

MIC400PAGUW14536P MIC Series 400 public address
Public address, 36X, PAL, PTZ camera, Grey, Upright, FV Protocol with integrated wiper and privacy function
Order number **MIC400PAGUW14536P**

MIC400PABUP14518N MIC Series 400 public address

Public address, 18X, NTSC, PTZ camera, Black, Upright, Bosch Protocol with integrated wiper and privacy function

Order number **MIC400PABUP14518N**

MIC400PABUP14536N MIC Series 400 public address

Public address, 36X, NTSC, PTZ camera, Black, Upright, Bosch Protocol with integrated wiper and privacy function

Order number **MIC400PABUP14536N**

MIC400PAGUP14518N MIC Series 400 public address

Public address, 18X, NTSC, PTZ camera, Grey, Upright, Bosch Protocol with integrated wiper and privacy function

Order number **MIC400PAGUP14518N**

MIC400PAGUP14536N MIC Series 400 public address

Public address, 36X, NTSC, PTZ camera, Grey, Upright, Bosch Protocol with integrated wiper and privacy function

Order number **MIC400PAGUP14536N**

Accessories**MIC-24PSU-UL 24 VAC Camera Power Supply**

24 VAC, 50/60 Hz power supply for MIC Series cameras

Order number **MIC-24PSU-UL**

MIC-115PSU-UL 115 VAC Camera Power Supply

115 VAC, 60 Hz power supply for MIC Series cameras

Order number **MIC-115PSU-UL**

MIC-240PSU-UL 240 VAC Camera Power Supply

230 VAC, 50 Hz power supply for MIC Series cameras

Order number **MIC-240PSU-UL**

MIC-BP4 Biphase Converter

Biphase converter for non-IR versions of MIC series power supply units

Order number **MIC-BP4**

MIC-DCA-B Deep Conduit Adapter, Black

Deep conduit adapter for 4 in. PCD base - black leatherette finish, RAL9005

Order number **MIC-DCA**

MIC-DCA-G Deep Conduit Adapter, Grey

Deep conduit adapter for 4 in. PCD base - grey leatherette finish, RAL9010

Order number **MIC-DCA-G**

MIC-SCA-B Shallow Conduit Adapter, Black

Shallow conduit adapter for 4 in. PCD base - black, leatherette finish, RAL9005

Order number **MIC-SCA**

MIC-SCA-G Shallow Conduit Adapter, Grey

Shallow conduit adapter for 4 in. PCD base - grey, leatherette finish, RAL7001

Order number **MIC-SCA-G**

MIC-SPR Spreader Plate

Aluminum spreader plate suitable for brickwork surface mounting – black leatherette finish RAL9005

Order number **MIC-SPR**

MIC-SPR-G Spreader Plate, Grey

Aluminum spreader plate suitable for brickwork surface mounting, grey leatherette finish (RAL7001)

Order number **MIC-SPR-G**

MIC-CMB-B Corner Mount Bracket, Black

Corner mount bracket, black leatherette finish (RAL9005)

Order number **MIC-CMB-B**

MIC-CMB-G Corner Mount Bracket, Grey

Corner mount bracket, grey leatherette finish (RAL7001)

Order number **MIC-CMB-G**

MIC-PMB Pole Mount Bracket

Pole mount bracket (includes 2 x 455 mm stainless steel banding straps for pole diameters 75 to 145 mm)

Order number **MIC-PMB**

MIC-WMB-B Wall Mount Bracket, Black

Wall mount bracket, black leatherette finish (RAL9005)

Order number **MIC-WMB-B**

MIC-WMB-G Wall Mount Bracket, Grey

Wall mount bracket, grey leatherette finish (RAL7001)

Order number **MIC-WMB-G**

MICUSB485CVTR2 USB to RS485 Signal Converter

USB to RS485 signal converter to allow MIC Series cameras to connect to a PC, supplied with each camera

Order number **MICUSB485CVTR2**

MIC-ALM Alarm and Washer Pump Drive Card

8 Input alarm and washer pump drive card for PSU (Not for IR PSU)

Order number **MIC-ALM**

MIC-WKT Washer Kit

Washer kit for non infrared MIC models (includes washer pump drive card, washer nozzle and mounting brackets for wall and 4 in. PCD base)

Order number **MIC-WKT**

UPA-2450-50 Power Supply, 220 V, 50 Hz

Indoor, 220 VAC, 50 Hz In; 24 VAC, 50 VA Out

Order number **UPA-2450-50**

UPA-2450-60 Power Supply, 120 V, 60 Hz

Indoor, 120 VAC, 60 Hz In; 24 VAC, 50 VA Out

Order number **UPA-2450-60**

MIC-2M-S 2 m Shielded Composite Cable

Shielded Composite 2 m cable that provides power, telemetry and video connection from a MIC Series camera to a MIC Series power supply

Order number **MIC-2M-S**

MIC-10M-S 10 m Shielded Composite Cable

Shielded Composite 10 m cable that provides power, telemetry and video connection from a MIC Series camera to a MIC Series power supply

Order number **MIC-10M-S**

MIC-20M-S 20 m Shielded Composite Cable

Shielded Composite 20 m cable that provides power, telemetry and video connection from a MIC Series camera to a MIC Series power supply

Order number **MIC-20M-S**

MIC-25M-S 25 m Shielded Composite Cable

Shielded Composite 25 m cable that provides power, telemetry and video connection from a MIC Series camera to a MIC Series power supply

Order number **MIC-25M-S**

HAC-WAS05-20 24 VAC Washer

24 VAC washer inst. 4M 25L

Order number **HAC-WAS05-20**

HAC-WAS30-50 230 VAC Washer

230 VAC washer inst. 30M 25L

Order number **HAC-WAS30-50**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com