

HDMI Over Single Cat5e/6

MVE-AH020Q Up to 164-ft. Range at 1080p Resolution

The MVE-AH020Q uses a single low-cost Cat5e/6 cable to transmit HDMI signals instead of heavier, less flexible and more expensive HDMI Cables.

Features:

- Connect HDMI equipment using a single lowcost Cat5e/6 cable.
- Works with 1080p high-definition video and audio up to 196ft (60m).
- Zero signal loss.
- Video formats supported: 480i/480p/576i/576p/720p/1080i/1080p
- ▶ Built-in equalization and signal-boost function.
- Auto adjusts the equalization and amplification to eliminate feedback.
- Compact size.
- ▶ 5VDC power supply included.

Specifications:


| Input video signal | | 0.5~1 Vp-p |
|---------------------------|-------------|---|
| Maximum single link range | | 1920 x 1200, 1080p |
| Output video | | HDMI 1.2a |
| Video formats supported | | 1080p/1080i/720p/576p/576i/480p/480i |
| Range | 1080p | Cat5e: 98' (30m) / Cat6: 164' (50m) |
| | 1080i,720p | Cat5e: 164' (50m) / Cat6: 197' (60m) |
| | 576p, 480p | Cat5e: 197' (60m) / Cat6: 213' (65m) |
| | 576i, 480i | Cat5e: 213' (65m) / Cat6: 230' (70m) |
| Current | Transmitter | 780mA@5VDC |
| draw | Receiver | 109mA@5VDC |
| Video amplifier bandwidth | | 1.65Gbps/165MHz |
| Vertical frequency range | | 50/60 Hz |
| Operating temperature | | 32°~158° F (0°~70° C) |
| Operating humidity | | 10~85 % RH (no condensation) |
| Size | | 3 ¹⁵ / ₁₆ "x2 ¹ / ₂ "x1" (100x65x25.5 mm) |
| Weight | | 13.6-oz (385g) |
| Power supply | | 2A@5VDC (2 adapters included) |



Sold in pairs: Each set contains one transmitter and one receiver.



Sample Application:



SECO-LARM

16842 Millikan Avenue Irvine, CA 92606 Tel: 1-949-261-2999 1-800-662-0800

Fax: 1-949-261-7326

Web: www.seco-larm.com

Email: info@seco-larm.com

Copyright © 2010 SECO-LARM U.S.A, Inc. All rights reserved