PROJECTOR MW85 I UST DIGITAL














Features

- Native WXGA (1280x800) Resolution
- 2500 ANSI Lumens; 13000:1 Contrast Ratio
- 0.36 Ultra Short Throw Ratio
- LAN Control: Smart Eco Mode
- IOW x 2 Speaker; SRS WOW HD™; Mic Input



Input and Output Terminals



- 1 LAN (RJ45)
- USB Mini B
- **3** RS232 (DB-9pin)
- 4 HDMI (v1.3)
- **6** Monitor Out (D-sub 15pin)
- 6 Computer In 1 & 2 (D-sub 15pin)
- S-Video In (Mini DIN 4pin)
- 8 Audio Out L & R (RCA)
- 9 Audio In 1 & 2 (Mini Jack)
- 10 Composite Video In (RCA)
- DC 12V Trigger (3.5mm)
- Audio Out (Mini Jack)
- Mic In (Mini Jack)

Specifications	
Projection System	DLP
Native Resolution	WXGA(1280x800)
Brightness	2500 ANSI Lumens
Contrast Ratio	13000:1
Display Color	1.07 Billion Colors
Lens	F=2.65
Aspect Ratio	Native 16:10 (5 aspect ratio selectable)
Throw Ratio	0.36 (95"@ 2.43 ft)
Image Size (Diagonal)	60"~300"
Zoom Ratio	Fixed
Lamp Type	UHP230W (with Smart Eco Mode)
Lamp Life (Nor/Eco/Smart Eco Mode)	3500/5000/ up to 6500 hrs
Keystone Adjustment	Manual, Vertical +/- 15 degrees
Projection Offset	144%+-5%
Resolution Support	VGA(640 x 480) to UXGA(1600 x 1200)
Horizontal Frequency	31K~102KHz
Vertical Scan Rate	23~120Hz
Compatibility	HDTV Compatibility: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p Video Compatibility: NTSC, PAL, SECAM
Interface	Computer in (D-sub 15pin) x 2 (shared with Component video)
	Monitor out (D-sub 15pin) x 1
	Composite Video in (RCA) x 1
	S-Video in (Mini DIN 4pin) x 1
	Audio in (Mini Jack) x 2
	Audio I/ (Will Jack) X 2 Audio L/R in (RCA) X 2
	Audio out (Mini Jack) x 1
	` '
	Speaker 10W x 2
	LAN (RJ45) x 1 (LAN Control)
	HDMI V1.3 x 1
	USB (Type Mini B) x 1 (USB Download & Page up/down)
	DC 12V Trigger (3.5mm Jack) x 1
	RS232 (DB-9pin) x 1
Dimensions (WxHxD)	13.35 x 9.33 x 12.71 inches (339 x 236.9 x 322.8 mm)
Weight	11.70 lbs (5.3kg)
Power Supply	100 to 240 VAC, 50 to 60 Hz
Power Consumption	Typical 321W, Standby<0.5W
Audible Noise	33/27 dBA (Normal/Economic mode)
On-Screen Display	English/ France/ Germany/ Italian/ Spanish/ Russian/ Traditional
Languages	Chinese/ Simplified Chinese/ Japanese/ Korean/ Swedish/ Dutch/
	Turkish/ Czech/ Portuguese/ Thai/ Polish/ Hungarian/ Croatian/ Romanian/ Norwegian/ Danish/ Bulgaria/ Finnish/ Indonesian/ Greek/
	Hindi/ Arabic (28 Languages)
Picture Mode	Dynamic/Presentation/sRGB/Cinema/User 1/User 2
Accessories (Standard)	Remote Control w/ Battery, Power Cord, User Manual CD, Quick Start
Accessories (Staridard)	Guide, Warranty Card, VGA (D-sub 15 pin) Cable
Accessories (Optional)	Spare Lamp Kit P/N: 5J.J4V05.001
Accessories (Optional)	Wall Mount (T/R 0.4) P/N: 5J.J4V10.001
	` '
Limited Warranty	3D Glasses P/N: 5J.J0T14.011 3 Years Parts/Labor; 1 Year or 2000 hours of lamp life
	o . ca.co. actor cubor, i rodi oi 2000 flouro di lump illo

^{*}Lamp life results will vary depending on environmental conditions and usage.

















MW851UST 01-04-12-BQus

BenQ is a registered trademark of BenQ Corp. DLP is a registered trademark of Texas Instruments. All rights reserved. Product names, logos, brands, and other trademarks featured or referred to in this materials are the property of their respec Specifications subject to change without notice.