

N3548 & N3748 Series

Eight Channel Digital Video Transmission System



Features

- 10 bits digitally encoded video transmission
- NTSC, PAL, and SECAM auto compatible
- Surface mount technology
- LED indicators for monitoring of system operating status
- Surge protection
- Highest optical dynamic range
- Immune to EMI and RFI
- Dense structure for easy installation
- Hot swappable rack mount cards
- Automatic re-settable fuses, short circuit protection
- 12 VDC or 24 VAC power supply
- Industry standard connectors
- No user adjustments required

Description

Infinova's N3548 and N3748 series provides the ability to transmit 8 digitally encoded video channels over one optic fiber.

Modular in design, the N3548 and N3748 series can be rack-mounted or used as a stand-alone module. Rack mounting requires N3910 series subrack. Stand-alone module is accomplished with N3910-2S and can be placed on a desktop or mounted to a wall.

North America
World Headquarters, USA
Infinova
51 Stouts Lane
Monmouth Junction, NJ 08852
United States

Phone:
+1 732-355-9100
+1 888-685-2002 (toll-free)
Fax: +1 732-355-9101
E-mail: Sales@infinova.com

Latin America & Caribbean
Miami: +1-954-990-0787
Mexico: +52-55-5543-5563
Venezuela: +58-414 205-0106
E-mail: Sales-LAR@infinova.com

Brazil: +55-41-3016-5503
E-mail: vendas-brasil@infinova.com

Argentina: +54-116-009-6009
E-mail: ventas@infinova.com.ar

Europe
Phone: +40 723 536600
E-mail: Sales-EUR@infinova.com

Asia Hong Kong
Phone: +852 2795 6540
E-mail: Sales-HK@infinova.com

Middle East & Africa
Phone: +965 2247 5678
E-mail: Sales-ME@infinova.com

India
+91 20 2669 8599
E-mail: Sales-IND@infinova.com

Ordering Information

N3548TA-M	FO MM TX, 8V In, Module, 12VDC/24VAC
N3548TA-R	FO MM TX, 8V In, Card, 2-Slot
N3548RA-M	FO MM RX, 8V Out, Module, 12VDC/24VAC
N3548RA-R	FO MM RX, 8V Out, Card, 2-Slot


N3748TA-M	FO SM TX, 8V In, Module, 12VDC/24VAC
N3748TA-R	FO SM TX, 8V In, Card, 2-Slot
N3748RA-M	FO SM RX, 8V Out, Module, 12VDC/24VAC
N3748RA-R	FO SM RX, 8V Out, Card, 2-Slot

Fiber Type	Optical Budget (dB)	Wavelength (nm)	Range (km)
Multi-mode	7	1310	2.2
Single-mode	17	1310	25
*Higher output lasers available for range over 25km			

Note:

1. Distance is limited to fiber loss, splices, chromatic dispersion and bandwidth
2. Range estimates are based on 1.0dB/km @ 1310nm on MM fiber, 0.35dB/km @ 1310nm on SM fiber, and include a 3dB safety factor
3. Range estimates for multimode are based on 1000MHz/km fiber

System Diagram



Accessories

Power Supply

N3921-12D-1:	12 VDC (120 VAC), 10 VA
N3921-12D-2:	12 VDC (230 VAC), 10 VA
N3921-24A-1:	24 VAC (120 VAC), 20 VA
N3921-24A-2:	24 VAC (230 VAC), 20 VA

Applications

- Smart buildings
- Security and surveillance
- Intelligent transportation system
- Highway surveillance system

Configurations

- Compact 2 slot modules and 2 slot card units
- 18 slots per 19" x 3U subrack; 100 W / 250 W power supply
- 15 slots per 19" x 3U subrack; 100 W / 250 W dual power supply

Specifications

Video Performance	Video Channel	8
	Video Input Impedance	75Ohm
	Video Voltage	1.0Vp-p
	Bandwidth	5Hz~6.5MHz
	Differential Gain	1% (typical)
	Differential Phase	1° (typical)
	Signal-to-Noise Ratio	67dB (weighted)
	PCM Encoding	10 bits
Optical Performance	Multi-mode	
	Output Power	-12dBm (typical)
	Receiver Sensitivity	-19dBm (typical)
	Wavelength	1310nm
	Connector	ST
	Single-mode	
	Output Power	-5dBm (typical)
	Receiver Sensitivity	-22dBm (typical)
	Wavelength	1310nm
	Connector	FC
LED Indicators	Power On	Red
	Optical Link Loss	Red
	Video Input/Output Presence	Green
General Parameters	Operating Temperature	-40°F ~ 167°F (-40°C ~ 74°C)
	Storage Temperature	-40°F ~ 185°F (-40°C ~ 85°C)
	Operating Humidity	0 ~ 95% RH (non-condensing)
	Card Dimensions (W ×H ×D)	1.57" x 5.08" x 6.73" (40mm x 129mm x 171mm)
	Module Dimensions (W ×H × D)	1.73" x 6.22" x 7.87" (44mm x 158mm x 200mm)
	Power Consumption	3.9W
	Card Weight	1.30lbs. (0.59kg)
	Module Weight	2.36lbs. (1.07kg)
	Mean Time Between Failures	>100,000 Hrs
Certifications	FCC: Part 15 Subpart B (Certificate No.: BCT09HC-715E)	
	CE/EMC: EN 55022, EN 55024, EN 61000-3-2, EN 61000-3-3 (Certificate No.: BCT09HC-714E)	
	ISO 9001:2008	
Compliance	UL, cUL	