

900007500Z_Outdoor Wireless AP_US

900007510Z_Outdoor Wireless AP_EU

Model and Product Description	
Outdoor Wireless Access Point , N600AG 900007500Z_US, 900007510Z_EU	
	
Wireless Standard	IEEE 802.11 a / b / g
Ethernet Standard	IEEE 802.3, IEEE 802.3u, IEEE 802.3af
Interface Operation Mode	Access Point (AP) / Wireless Station (AP Client)
System Operation Mode	Bridge / Transparent Bridge / Router
SDRAM	64Mbyte
Flash	16Mbyte
Max. Bandwidth	Full Duplex : 100Mbps (100Base), 10Mbps (10Base) Half Duplex : 50Mbps (100Base), 5Mbps (10Base)
Wireless Transmission Rate	802.11 b/g : 11, 5.5, 2, 1 Mbps, Auto-fallback, up to 54Mbps 802.11 a : 54, 48, 36, 24, 18, 12, 9, 6 Mbps, Auto-fallback
Transmitted Power	802.11b Mode : 17dBm 802.11g Mode : 17dBm @ 6Mbps, 15dBm @54Mbps 802.11a Mode : 15dBm @ 6Mbps, 13dBm @54Mbps
Product Operate Setting	
Feature	Main Feature : (1).Daisy Chain (2).DC-Mesh (3).Trunk Special Feature : (1).Bridge Mode LAN DHCP (2).Dynamic WAN/LAN (3).Multiple RF Module (4).Multiple ESSID (VLAN) (5).Multicast Filter (6).Wireless Limited / Fixed Rate (7).Wireless Multicast Rate (8).Max RF Distance (9).Wireless Bandwidth Control (10).QoS (11).Wireless Survey (12).SNMP (13).NTP Command Line : (1).rateadaption (2).alt (3).nodeinfo (4).wlosthreshold (5).wlretry (6).apbmcfiler (7).brstp (8).wlmtoucast (9).mcastforward (10).mintxrate (11).mgmtvid (12).ethervid (13).pureg (14).cpeport (15).pac (16).pppoeflag

Security	Main Security : (1).MS NetBIOS Filter (2).Access ESSID (3).Hide ESSID (4).WEP-64/128/152bit (5).802.1x EAP-TLS / EAP-MD5 (6).WPA-PSK / WPA-EAP (7).MAC Address Access / Filter (8).RADIUS Server Client (9).Maximux AC connection Number Special Security : (1).Isolation (2).pac (3).mgmtvid (4).ethervid (5).service (6).pppoe flag
Consol	RS-232 Port
Antenna	Reversed N-type (Option)
Antenna Connector	2* Reversed Female N-type
Ethernet Connector	1*10/100 Base-T RJ-45 Power over Ethernet (PoE)
Power	DC 48Volt / 1A ; AC Adapter 100V~240V Power over Ethernet (PoE)
Operating Temp	-30 - 65°C
Storage	-40 - 80°C
Humidity	0% ~ 95% Non-condensing
Dimension	L*W*H : 226*197*79 mm
Weight	1700g
Dusty & Waterproof	IP68
US	FCC Part 15 Class B & C & E
Europe	EN 300 328, EN 301 489-1&17, EN 301 893, EN 60950 Compliant and CE Mark
Package Contents	
Feature	(1). 802.11a/b/g Outdoor Wireless AP (2). PoE Injector / Power Adapter & AC Power Cord (3). 30M MIL-C-5015 IP67 Cat-5 Ethernet Cable (4). 2M MIL-C-5015 IP67 RS-232 Consol Cable (5). Consol Port Waterproof cover (6). Wall Mounting Kit & Screw (7). Mast Mounting Kit & Screw (8). CD: User Manual (9). Quick Installation Guide (10). Grounding Wire