

Digital Power Amplifier Specifications

Power Output

Continuous Average Output Power	4 x 60W
Four channels driven 20-20kHz @1% THD	0.02%
Rated Distortion (1/2 power)	Switch Selectable 4 or 8 Ohms
Rated Impedance	50+
Damping Factor	±1 dB
Frequency Response (20-20kHz)	

Power-On Modes

Audio
Power
Trigger

System

Trigger Input	3-30 V AC or DC
Unit On Output	+12VDC @100mA

Source Inputs

Input Impedance	22k ohm
Input Sensitivity for rated power	.3-2V RMS
Input Overload	2.4V RMS

Power Requirements

Power Supply	100-240VAC 50/60Hz
Power Consumption both channels at maximum available output	340W
Power Consumption average operating conditions	50W
Power Consumption no signal	12W
Standby Power Consumption	0.35W

CE EMC
CE LVD
USA FCC
ETL
Canada Safety Listing (CAN/CSA E60065.00)
Australia C-Tick

Physical Specifications

Unit Size Millimeters	44 H x 430 W x 250 D
Unit Size Inches	1 3/4 H x 17 W x 9 7/8 D
Shipping Size Millimeters	205 H x 515 W x 343 D
Shipping Size Inches	8 H x 20 1/4 W x 13 1/2 D
Unit Weight Kilograms	3.0
Unit Weight Pounds	6.6
Shipping Weight Kilograms	4.8
Shipping Weight Pounds	10.5

NuVo reserves the right to change specifications without notice.