

Omnican OC-55

- Patented Omniguide technology creates immersive 360-degree sound dispersion
- Perfect for in-ceiling complete home theater application
- Indoor or outdoor installation; weather resistant construction
- Rotatable Omniguide module allows fine-tuning of sound in the listening area
- Low profile design
- Woofers feature patented Ribbed Elliptical Surround for increased output and lower distortion
- Easy installation and set up
- Removable back boxes for ease of installation in tight spaces
- Paintable grille and bezel



Specifications	
DESIGN:	Weather resistant Omnipolar in-ceiling speaker
SYSTEM TYPE:	2-Way
RECOMMENDED AMPLIFIER POWER:	10 to 125 Watts
NOMINAL IMPEDANCE:	8 Ohms
MINIMUM IMPEDANCE:	4 Ohms
FREQUENCY RESPONSE (+/- 3DB):	80 Hz - 20 kHz
SENSITIVITY (1W/1M):	89 dB
CROSSOVER POINT:	2.5 kHz
TWEETER:	1" PTH pure titanium hybrid tweeter
WOOFER:	5.5" titanium deposit polypropylene woofer with patented Ribbed Elliptical Surround
HEIGHT:	7.28" / 18.48 cm (1.6" / 4cm visible height when installed)
WIDTH:	W - 8.03" / 20.4 cm (back box) W- 9.43" / 23.96 cm (outside baffle)
RECOMMENDED HOLE CUT-OUT:	Ø 8.15 / 20.7 cm
REQUIRED INSTALLATION DEPTH:	5.43" / 13.8 cm (with back box installed) 2.87" / 7.3 cm (without back box)
CONNECTORS:	High quality spring loaded
PACKAGING QUANTITY:	1 per box
COLORS:	White
OTHER UNIQUE FEATURES:	Weather resistant design with UV-rated enclosure. Rotatable Omniguide module. Removable back box for installations with limited mounting depth
OPTIONAL INSTALLATION BRACKET:	ICB-55