



**PREFERRED
POWER
PRODUCTS**

P3DC15-4-3L

Specification Sheet

4 Camera 6-15VDC 2.5 Amp Power Supply

DESCRIPTION

The P3DC15-4-3L is a UL listed CCTV power center engineered to manage remote camera and accessory power requirements. The P3DC15-4-3L distribution module is designed with 4 individually fused outputs for powering up to 4 CCTV cameras and accessories.


It will provide 6-15 VDC via distribution to four fused outputs with a total of 2.5 Amps continuous supply current. The P3DC15-4-3L power center is housed in the premium P3 lockable heavy gauge metal enclosure.



FEATURES

- Convenient screw terminal and fuse access.
- Power ON/OFF switch.
- AC power LED indicator.
- Individual LED's for each fused output.
- Lockable heavy gauge metal enclosure.
- Double coated polyurethane finish.
- Multiple knockouts to accommodate various wiring configurations.
- Uses easy to find automotive style fuses.
- 6 to 15 VDC field adjustable.
- Requires a transformer.
- **Model P3DC15-4-3:** Includes open frame transformer, non-UL.
- **Model P3DC15-4-3LT:** Includes P3 24VAC 50 VA plug in transformer.

SPECIFICATIONS

- Input 115VAC 50/60 HZ; 1.0 Amps.
- Four 6 to 15VDC individually fused outputs.
- 2.5 Amps 6-15VDC supply currents at 70°F.
- Output fuses are rated at 1 Amp.
- UL listed  us
- Enclosure Dimensions: 10" (H) x 9" (W) x 4.5" (D).