



PD-D600-210

1/3" Color Varifocal Dome
Camera with 600 TV Lines



FEATURES:

- 1/3" Color Super HAD II CCD
- 600 TV Lines of Resolution (Color) / 650 TVL (B/W)
- Advanced DSP Features Including: DNR (Digital Noise Reduction), SBLC (Super Back Light Compensation), Image Mirror, Privacy Zones and Motion Detection
- Min. Illumination of 0.005 Lux (B/W)
- 2.8-10.5mm Varifocal Lens
- Secondary Video Output for ease of Installation
- 3-Axis Camera Gimbal Mounting
- 12VDC/24VAC Dual Voltage Operation
- Available with Black or White Base

SPECIFICATIONS:

IMAGE SENSOR	1/3 inch High Sensitivity CCD
HORIZONTAL RESOLUTION	600 TV Lines (BW 650TV Lines)
SCANNING SYSTEM	2:1 Interlace
SCANNING FREQUENCY(H)	15.734 KHz
SCANNING FREQUENCY(V)	59.94 Hz
SYNC. SYSTEM	Internal
TOTAL PIXELS NUMBER	811(H) x 508(V) 410K
EFFECTIVE PIXELS NUMBER	768(H) x 494(V) 380K
VIDEO OUTPUT LEVEL	1.0 Vp-p (75Ω, Composite)
S/N RATIO	More than 50dB (AGC Off)
LENS	DC Iris Vari-focal Lens (f=2.8~10.5mm)
MIN. ILLUMINATION	0.05 Lux (Color), 0.005 Lux (B/W), F1.2, 30IRE
DAY & NIGHT SYSTEM	ICR(AGC Type)
DIGITAL NOISE REDUCTION (SDNR)	Low, Middle, High, Off
WHITE BALANCE	ATW, Manual, Push
AGC	On/Off
SBLC	Off, Low, Middle, High
FLICKERLESS	On/Off
OSD MENU	English, Chinese
MIRROR FUNCTION	Horizontal
PRIVACY ZONE	On/Off (4 Programmable Zone)
MOTION DETECTION	On/Off (4 Programmable Zone)
ELECTRONIC SHUTTER SPEED	1/60~1/120,000
MANUAL SHUTTER SPEED	1/60, 1/250, 1/700, 1/1K, 1/1.6K, 1/2.5K, 1/5K, 1/7K, 1/10K, 1/30K, 1/60K, 1/120K
POWER VOLTAGE	12VDC (10V~15V)
POWER CONSUMPTION	Max. 2.2W/180mA
DIMENSIONS (H x D)	4.84" x 3.74" (123 x 95 mm)
WEIGHT (NET)	12.91 oz. (366g)