



PD-L-DVR Series

4, 8, & 16 Channel H.264
Digital Video Recorders



PD-L-DVR4



PD-L-DVR8



PD-L-DVR16

FEATURES:

- 4, 8, & 16 Channel Digital Video Recorders
- H.264 Compression for High Quality Video Recording with Minimal File Size
- Mobile surveillance on many popular mobile platforms including iPhone, BlackBerry, Android & WinCE
- Remote Viewing with Popular Web Browsers Including Internet Explorer, Firefox, Chrome, and Safari
- Up to 10 Concurrent Remote Users (8 & 16-Channel Models) / 5 Concurrent Remote Users (4-Channel Model)
- 120 FPS Recording with Real-Time Display (4-Channel Model), 240 FPS (8-Channel Model), 480 FPS (16-Channel Model)
- Individual Recording Settings per Channel
- Supports Internal SATA Hard Drives up to 2TB Each
- 4 Channel Audio Input on all models
- USB 2.0 Ports for External Backups
- Multiplex Operation: Live Display, Record, Playback, Backup, Network Operations



Remote Viewing Software



PD-L-DVR Series

4, 8, & 16 Channel H.264 Digital Video Recorders

SPECIFICATIONS:		PD-L-DVR4	PD-L-DVR8	PD-L-DVR16
VIDEO SYSTEM		NTSC / PAL (auto detection)		
VIDEO COMPRESSION FORMAT		H.264		
VIDEO INPUT (BNC)		4 channels	8 channels	16 channels
VIDEO OUTPUT (BNC)		Only 1 BNC		
VIDEO OUTPUT (VGA)		1 Built-in VGA interface for LCD monitor		
AUDIO		4 audio input / 1 audio output		
RECORDING RATE (MAX)		D1: 704×480 px @ 30 IPS Half-D1: 704×240 px @ 60 IPS CIF: 352×240 px @ 120 IPS	D1: 704×480 px @ 60 IPS CIF: 352×240 px @ 240 IPS	D1: 704×480 px @ 120 IPS CIF: 352×240 px @ 480 IPS
IMAGE QUALITY SETTING		SUPER BEST / BEST / HIGH /NORMAL		
HARD DISK STORAGE		1 SATA HDD (capacity up to 2TB)	2 SATA HDDs (Up to 2TB Each)	
QUICK SEARCH		Time / Motion / Alarm search mode		
SATA INTERFACE		Built-in		
VGA INTERFACE		Built-in		
RECORDING MODE		Manual / Timer / Motion / Alarm / Remote		
MULTIPLEX OPERATION		Live display / record / playback / backup / network operations		
USB MOUSE CONTROL		YES		
MOTION DETECTION AREA		16 × 12 grids per camera for all channels		
MOTION DETECTION SENSITIVITY		3 adjustable parameters for accurate detection		
PRE-ALARM RECORDING		YES		
BACKUP DEVICE		USB 2.0 flash drive / Network	DVD Writer (Optional) / USB 2.0 flash drive / Network	
ETHERNET		10/100 Base-T. Supports remote control and live view via Ethernet		
WEB INTERFACE		Supports licensed software "Video Viewer" / QuickTime player / Web Browsers (Including: IE, FireFox, Chrome)		
REMOTE USERS		5 users simultaneously	10 users simultaneously	
NETWORK PROTOCOL		TCP/IP, PPPoE, DHCP and DDNS		
REMOTE OPERATION		YES		
EVENT NOTIFICATION		By FTP / E-Mail		
IR REMOTE CONTROL		YES (IR receiver built-in)		
MOBILE SURVEILLANCE		YES (including iPhone, BlackBerry, WinCE, J2ME & Android)		
PICTURE ZOOM		2X digital zoom		
PTZ CONTROL		NO	YES	
ALARM I/O		4 inputs, 0 output	8 inputs, 1 output	16 inputs, 1 output
KEY LOCK		YES (Password Protection)		
LOCAL USER LEVEL		Administrator & Operator		
VIDEO LOSS DETECTION		YES		
CAMERA TITLE		Supports up to 12 Characters		
VIDEO ADJUSTABLE		Hue / Saturation / Contrast / Brightness		
DATE DISPLAY FORMAT		YY/MM/DD, DD/MM/YY & MM/DD/YY		
DAYLIGHT SAVING		YES		
SYSTEM RECOVERY		System auto recovery after power failure		
OPTIONAL PERIPHERALS		N/A		
POWER SOURCE (±10%)		DC 19V		
POWER CONSUMPTION (±10%)		< 42 W	< 64 W	
OPERATING TEMPERATURE		50 F~104 F (10 C ~ 40 C)		
DIMENSIONS (W x H x D)		13.50" x 2.32" x 8.77"	17.01" x 3.54" x 12.83"	