PMC Series Mounts WALL/CEILING/RACK MOUNTS, MONITORS

Product Features

- Single Swing-Arm Wall Mount
- For Use with VESA[®]-Compliant Monitors and Selected PMCL500 Series LCD Monitors
- Rack Mounts for All 200/300/400 Series LCD Monitors
- Fixed and Tilt Wall Mount for PMCL524F, PMCL532F, PMCL542F, PMCL547F, and PMCL552F Monitors
- VESA-Compliant Wall and Ceiling Mounts
- Can Be Used with Pelco Series LCD Monitors
- Unique Tilt/Swivel Head Design Ensures Optimum Viewing Angle
- · Easy to Install
- Aluminum or Steel Construction
- For Indoor Applications Only

Pelco's family of monitor mounts has been designed for use with VESA®-compliant monitors. Mounts for the **PMCL 200/300/400/500 Series** monitors include several wall and ceiling mounts. Three rack mounts are available for 200/300/400 Series monitors. Many of the mounts feature a unique tilt/swivel capability, which allows an LCD monitor to be swiveled 360 degrees for portrait or landscape viewing and tilted 35 degrees up or down. This tilt/swivel quality ensures the proper viewing angle in any application. Made from heavy-duty aluminum, these mounts are designed to support up to 90 pounds in any indoor installation.

The **PMCL-WM** and **PMCL-WMT** are two-piece wall mounts. One piece attaches to the rear of any monitor, and the other piece fastens to a wall. The monitor then slides into the V-shaped piece on the wall, making installation quick and easy. A setscrew secures the two sections together. The **PMCL-WMF** is a flat wall mount used for Full High Definition (FHD) monitors. The **PMCL-WMT** is equipped with tilt/swivel capabilities, while the **PMCL-WMTF** is tilt only for FHD monitors.

The **PMCL-WM1A** is a single-arm wall mount that is equipped with convenient tilt/swivel swing arms, which provides greater viewing flexibility.



PMCL-WM1A SINGLE-ARM WALL MOUNT AND PMCL SERIES MONITOR

The tilt/swivel **PMCL-CMP** allows an LCD monitor to be mounted from the ceiling. It is equipped with an adjustable 15- to 30-inch (38 to 76 cm) telescoping pole. The **PMCL-CM** is a similar ceiling mount that does not include a pole. This mount allows a customer to purchase any length of 1.5-inch NPT threaded pipe for use in applications with higher ceilings. Both of these ceiling mounts can also be used with Pelco's MRCA ceiling mount.

The **PMCL-VAF** is an adapter plate that attaches to the **PMCL-CM** ceiling mount and **PMCL-CMP** ceiling mount with pole. This adapter plate allows the mounts to be used with larger format monitors, such as Pelco's **PMCL542F** and **PMCL547F** monitors. It accommodates monitors with 600 x 400 mm hole patterns.

The **PMCL-V200** is an adapter plate that attaches to the **PMCL-WM, PMCL-WMT, PMCL-WM1A, PMCL-CM**, and **PMCL-CMP**. This adapter plate allows the mounts to be used with the **PMCL532F** larger format monitor. It also accommodates monitors with 200 x 200 mm hole patterns.

There are three rack mount kits for installing monitors in standard 19-inch (48 cm) equipment racks: the **PMCL-17ARM, PMCL-19ARM,** and **PMCL-19WRM,** which accommodate the 17-inch (43 cm), 19-inch (48 cm), and the 19-inch (48 cm) wide monitors, respectively. These mounts allow the monitor to tilt up or down for optimum viewing.



International Standards Organization Registered Firm; ISO 9001 Quality System C2219 / REVISED 8-10-10

by Schneider Electric

WALL MOUNTS

MODELS

PMCL-WMT PMCL-WM PMCL-WM1A PMCL-WMTF PMCL-WMF Tilt/swivel single-arm wall mount Fixed wall mount Tilt/swivel single-arm wall mount Tilt wall mount for large FHD monitors Flat wall mount for large FHD monitors

MECHANICAL

Swivel Adjustment Tilt Adjustment

CERTIFICATIONS

UL/cUL Listed


PMCL-WMT and PMCL-WM1A only


360° (PMCL-WMT, PMCL-WM1A only)


35° (PMCL-WMT, PMCL-WM1A only)



PMCL-WMT












PMCL-WM





GENERAL Suggested Mour

| Suggested Mounting Method PMCL-WM, PMCL-WMT | Secure to solid surfar diameter x 2-inch we In applications where encountered, use fou 2-inch lag bolts or tw | hardware is not supplied. colid surface with four 1/4-inch 2-inch wedge anchors. ons where wall studs are d, use four 1/4-inch diameter x bolts or two lag bolts and two ameter x 2-inch toggle bolts. colid surface with three 5/16-inch | | | | |
|---|---|--|--|--|--|--|
| PMCL-WM1A | Secure to solid surface with three 5/16-inch diameter x 2-inch wedge anchors or use three 5/16-inch diameter x 2-inch lag bolts in applications where wall studs are encountered. | | | | | |
| PMCL-WMF, PMCL-WMFT | Attach the mount bracket to a solid wall using eight screws that are able to hold 264.6 lb (120 kg). | | | | | |
| Maximum Load PMCL-WM PMCL-WMT, PMCL-WM1A PMCL-WMF PMCL-WMTF | eight screws that are able to hold 264.6 lb (120 kg). 35.00 lb (15.88 kg) | | | | | |
| Construction | | | | | | |
| PMCL-WM, PMCL-WMT, PMCL-WM1A PMCL-WMF, PMCL-WMFT | Aluminum Steel | | | | | |
| Finish | Black polyester powder coat | | | | | |
| Weight PMCL-WMT PMCL-WM PMCL-WM1A PMCL-WMF PMCL-WMTF | Unit 3.05 lb (1.38 kg) 1.60 lb (0.73 kg) 3.55 lb (1.61 kg) 11.24 lb (5.10 kg) 4.80 lb (2.17 kg) | Shipping 6 lb (2.72 kg) 3 lb (1.36 kg) 6 lb (2.72 kg) 13 lb (5.89 kg) 6 lb (2.72 kg) | | | | |



NOTE: VALUES IN PARENTHESES ARE CENTIMETERS; ALL OTHERS ARE INCHES.

CEILING MOUNTS

MODELS

PMCL-CM

PMCL-CMP

MECHANICAL

Swivel Adjustment Tilt Adjustment

360° 90°

LCD monitors

GENERAL

Suggested Mounting Method

Wood Beam Metal I-Beam


Concrete

Maximum Load Construction Finish Weight PMCL-CM PMCL-CMP

CERTIFICATIONS

• UL/cUL Listed





Ceiling mount and VESA head for

Ceiling mount and VESA head with

telescoping pole for LCD monitors

RACK MOUNTS

MODELS

| PMCL-17ARM | Kit for mounting a 17-inch (43 cm) monitor in a 19-inch (48 cm) equipment rack |
|------------|--|
| PMCL-19ARM | Kit for mounting a 19-inch (48 cm) monitor in a 19-inch (48 cm) equipment rack |
| PMCL-19WRM | Kit for mounting 19-inch (48 cm) wide monitor in a 19-inch (48 cm) equipment rack |

 $\ensuremath{\text{Note:}}$ The kits include two brackets, eight M4X0.7 screws, and one installation manual.


Mild steel

GENERAL

Construction Finish Dimensions PMCL-17ARM PMCL-19ARM PMCL-19WRM

Unit Weight Shipping Weight Black polyester powder coat 1.95" D x 18.90" W x 13.91" H (4.96 x 48.00 x 35.33 cm) 1.95" D x 18.90" W x 15.67" H (4.96 x 48.00 x 39.79 cm) 1.95" D x 18.90" W x 13.90" H

(4.96 x 48.00 x 39.79 cm) 1.95" D x 18.90" W x 13.90" H (4.96 x 48.00 x 35.31 cm) 1.10 lb (0.50 kg) Consult the factory



(9.436)



PMCL-19ARM

NOTE: VALUES IN PARENTHESES ARE CENTIMETERS; ALL OTHERS ARE INCHES.

ADAPTER

MODEL

PMCL-V200


PMCL-VAF


Converts 200 x 200 mm to 100 x 100 mm VESA pattern. (Required for use with the PMCL532F and Pelco monitor mounts with 200 x 200 VESA pattern.) Converts a 600 x 400 mm to 100 x 100 mm VESA pattern. (Required for use with PMCL542F, PMCL547F, and Pelco monitor mounts with a 600 x 400 mm pattern.)

GENERAL

Suggested Mounting Method PMCL-V200 Secure to PMCL mount using 10-32 x 0.75-inch Phillips screws (supplied) PMCL-VAF Secure to PMCL mount using M16 x 12 mm screws (supplied) Construction PMCL-V200 Aluminum PMCL-VAF Steel Finish Black polyester powder coat Weight Unit Shipping PMCL-V200 1.0 lb (0.45 kg) 3 lb (1.36 kg) PMCL-VAF 9.9 lb (4.49 kg) 12 lb (5.44 kg)







NOTE: VALUES IN PARENTHESES ARE CENTIMETERS; ALL OTHERS ARE INCHES.

LCD MOUNT SELECTION GUIDE

| | | Compatible Monitors | | | | | | | | | | |
|------------|-----------------------------------|---------------------|----------|----------|----------|----------|----------|----------|----------|----------------|----------------|----------|
| Model | Description | PMCL219A | PMCL317A | PMCL319A | PMCL319W | PMCL417A | PMCL419A | PMCL524F | PMCL532F | PMCL542F | PMCL547F | PMCL552F |
| PMCL-WM | Fixed Wall Mount | • | • | • | • | • | • | • | •* | | | |
| PMCL-WMT | Tilt/Swivel Wall Mount | • | • | • | • | • | • | • | •* | | | |
| PMCL-WMF | Flat Wall Mount for FHD Monitors | | | | | | | | | • | • | • |
| PMCL-WMTF | Tilt Wall Mount | | | | | | | | | • | • | • |
| PMCL-WM1A | Tilt/Swivel Single-Arm Wall Mount | • | • | • | • | • | • | • | •* | | | |
| PMCL-CM | Ceiling Mount | • | • | • | • | • | • | • | •* | • [†] | •† | |
| PMCL-CMP | Ceiling Mount with Pole | • | • | • | • | • | • | • | •* | • [†] | • [†] | |
| PMCL-17ARM | 17-inch Monitor Rack Mount | | • | | | • | | | | | | |
| PMCL-19ARM | 19-inch Monitor Rack Mount | • | | • | | | • | | | | | |
| PMCL-19WRM | 19-inch Wide Monitor Rack Mount | | | | • | | | | | | | |
| PMCL-VAF | 600 mm X 400 mm Adapter Plate | | | | | | | | | • | • | |
| PMCL-V200 | 200 mm X 200 mm Adapter Plate | | | | | | | | • | | | |

*PMCL-VAF adapter plate needed.

[†]PMCL-V200 adapter plate needed.