





66-5218CSE

FEATURES:

- Indoor/Outdoor installation.
- High efficiency infrared LED, radiant distance
 - 18 meters.
- Sensor auto activate infrared LED under 10lux light level.
- Aluminum housing case with IP68 rating.
- Improve the image quality in low-light situations and in complete darkness.



SPECIFICATIONS:

| | INFRARED ILLUMINATOR | | |
|--|-----------------------|-----------------|--------------------------------|
| | Model No. | | PRH-5218 |
| | Power Input Voltage | | DC12V (±10%) |
| | Radiant Distance | | 18M (59ft) |
| | Infrared LED | Peak Wavelength | 850nm |
| | | Quantity | 21 Units |
| | | Angle | 30° |
| | | Power On | Sensor Auto Control |
| | Window | | ϕ 59 Heat Resistant Glass |
| | IP Rating | | IP68 |
| | Construction | | Aluminum |
| | Power Consumption | | 2.0W |
| | Operating Temperature | | -20°C ~ +60°C (-4°F ~ +140°F) |
| | Dimension | | ϕ 65 x 65.1 mm |
| | Weight | | 160g |

- * To use this illuminator with third party's AC adaptor, please make sure that the adaptor contains built-in DC regulator. An AC adaptor without built-in DC regulator can damage this illuminator.
- * Any attempt to disassemble the illuminator may hamper the waterproof ability of the illuminator.
- * Design and specifications are subject to change without notice.