



# POWER MASTER RED DOUBLE GANG STROBE MODEL RST2G-R

## REVERE INDUSTRIES

REVERE INDUSTRIES • 1101 BIENVILLE STREET • NEW ORLEANS, LA 70112  
504 523-3503 • 800 843-8321 • 24-HOUR FAX ORDER LINE 800 511-1821

U.S. and International Patents applied for. UL-464  
Fire Alarm and General Signaling Service pending

### SPECS AT A GLANCE

Operating Voltage .....12VDC  
Current Draw .....125 mA  
Mounting .....Use double gang electrical box or Revere  
Surface Mount Adaptors R200SM  
Candle Power .....100,000 CP  
Material .....UL-94 flame retardant plastic  
Color .....Decorator White  
Dimensions .....4 $\frac{1}{2}$ " H x 4 $\frac{1}{2}$ " W x 1" D  
Lens Supplied .....Red

Optional lens kit available:

**RST456L/ABG**

- 1 – Amber lens
- 1 – Blue lens
- 1 – Green lens



Note: To change lens, remove the present lens by gently prying the strobe from the plate. Do this by working from the rear of the plate; if done from the front the plate may be damaged. When installing the new lens make sure it is oriented properly. The curved side of the lens mates with the curved lip on the plate.

### DESCRIPTION



The **RST2G-R** is a strobe on a double gang wall plate. It can be flush mounted with or without using a double gang electrical box. The RST2G-R can also be mounted using the **REVERE** R200SM surface mount adaptor. When using the R200SM mount adaptor, two R123ST or two RST456SQ strobes can be added for a total of 3 strobes on one surface mount adaptor.