



ENGINEERED GROUNDED PLUG-IN TRANSFORMER with LED and FULL SURGE PROTECTION RT-G1220SL/M

REVERE INDUSTRIES

REVERE INDUSTRIES • 1101 BIENVILLE STREET • NEW ORLEANS, LA 70112
504 523-3503 • 800 843-8321 • 24-HOUR FAX ORDER LINE 800 511-1821



BAR CODED

SPECS AT A GLANCE

- UL Listed
- Primary120VAC 60Hz
- Secondary12VAC, 20VA
- LED IndicatorSupervises power
- Primary Termination.....2 Male Blades and
Grounding Pin
- Secondary Termination3 #6-32 Screw Terminals
with washers for secure
contact
- Size2 1/4" W x 2" D x 3 5/8" H
- Weight.....1 lb.
- ColorBright Decorator White

Surge Protection Specs

- 3 Mode ProtectionLine, Neutral, Ground
- Clamping Voltage.....340V
- Max. Spike Current4500 Amps
- Energy Dissipation.....60 Joules
- Max. Spike Voltage6000 Volts
- Clamping Response Time25 Nanoseconds



DESCRIPTION

The **REVERE ENGINEERED™** RT-G1220SL/M is a 12VAC, 20VA Class II U.L. Encased Plug-in Transformer with LED indicator for power supervision, built in cable strain relief, and with full surge protection. Its construction is a bright decorator white colored plastic. It comes with a mounting tab and mounting screw. The compact design, as well as its decorator color, makes it perfectly suitable for office or residential decors.