



VALUE LINE
FLUSH OR SURFACE MOUNT SPEAKER
WITH DUAL CHANNEL SIREN DRIVER
MODEL RVL-15IN/SRN

REVERE INDUSTRIES

REVERE INDUSTRIES • 1101 BIENVILLE STREET • NEW ORLEANS, LA 70112
504 523-3503 • 800 843-8321 • 24-HOUR FAX ORDER LINE 800 511-1821

SPECS AT A GLANCE

U.S. and International Patents applied for. UL-464
Fire Alarm and General Signaling Service pending

- Speaker Polypropylene
- Speaker Rating 15 Watts
- Operating Voltage 12 VDC
- Current Draw 600 mA
- Channel Capacity 2-Channel Siren Speaker with
Pulsing Fire Horn Sound
- Sound Level 100dB @ 10 ft.
- Color Decorator White
- Dimensions Surface Mount:
5¹/₄" x 5¹/₄" x 1³/₄"
Flush Mount:
5¹/₄" x 5¹/₄" x ³/₄"
- Material High Impact ABS Plastic
- Mounting Surface Mount: With screws and
anchors to wall or mount to single
and double gang electrical box
Flush Mount: Discard back of
housing and use screws and
anchors to mount to wall



UL Listing pending
Patent applied for

DESCRIPTION



The RVL-15IN/SRN 2-channel siren speaker with pulsing fire horn is an audible signal appliance designed for flush or surface mounting. It is ideally suited for alarm signaling indoors.