

Overview



ReServ3
(order batteries separately)

ReServ3 Video Surveillance UPS is designed to provide power for 12VDC cameras during normal or power outage conditions. Regulated DC outputs.



Specifications

Input:

- 115VAC 60 Hz, 3.5 amps.

Output:

- 16 individually PTC protected outputs.
- 12VAC @ 8 amp total supply current (Amb. Temp. -33° - 42° C).
- PTC protected power-limited outputs are rated @ 1 amp.

Battery Backup:

- Built-in charger for sealed lead acid or gel type batteries.
- Automatic switchover to stand-by battery when AC fails.

Stand-by Batteries	8 amp load at 12VDC max.
Two (2) 12VDC/7AH	45 minutes
Two (2) 12VDC/12AH	90 minutes

Supervision:

- AC fail supervision (form “C” contacts).
- Low battery supervision (form “C” contacts).

Visual Indicators:

- AC/DC power LED indicators.
- Individual power output LED indicators.
- Low voltage input and Shutdown LED indicators.

Additional Features:

- Regulated DC outputs.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

Enclosure Dimensions:

- Enclosure accommodates up to two (2) 12VDC/7AH batteries.
13.5”H x 13”W x 3.25”D

Product weight (approximate): 10.36 lbs.

Shipping weight (approximate): 11.26 lbs.

Agency Approvals



UL/CUL Listed for Information Technology Equipment (UL 60950-1).



European Conformity

Enclosure Dimensions (approximate)

13.5”H x 13”W x 3.25”D

