

Overview



ReServ3WP Video Surveillance UPS is designed to provide power for 12VDC cameras during normal or power outage conditions. Regulated DC outputs.



ReServ3WP

Specifications

Input:

- 115VAC 60 Hz, 3.5 amps.

Output:

- 16 individually PTC protected outputs.
- 12VAC @ 8 amp total supply current (Amb. Temp. -33° - 42° C).
- PTC protected power-limited outputs are rated @ 1 amp.

Battery Backup:

- Built-in charger for sealed lead acid or gel type batteries.
- Automatic switchover to stand-by battery when AC fails.

Stand-by Batteries	8 amp load at 12VDC max.
Two (2) 12VDC/7AH	45 minutes
Two (2) 12VDC/12AH	90 minutes

Supervision:

- AC fail supervision (form "C" contacts).
- Low battery supervision (form "C" contacts).

Visual Indicators:

- Individual power LED indicator.
- AC input power output LED indicators.
- Low battery and output power shutdown LED indicators.

Special Features:

- Regulated DC outputs.
- Audible alarm provides notification of UPS trouble conditions.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

Enclosure:

- NEMA4 / IP66 Rated Enclosure accommodates up to two (2) 12VDC/12AH batteries.
- Enclosure dimensions: 17.5"H x 12"W x 6.625"D

Weight (approximate):

- Product weight: 21.5 lbs.
- Shipping weight: 23 lbs.

Agency Approvals



UL/CUL Listed for Information Technology Equipment (UL 60950-1).



European Conformity

Enclosure Dimensions (approximate)

17.5”H x 12”W x 6.625”D

