

# Nextiva

## S4300 Wireless Access Point



### At A Glance:

- Transmits video from virtually anywhere using 2.4 or 5 GHz wireless band or 4.9 GHz US or Canada public safety band
- Compact, weatherproof enclosures that make them ideal for outdoor use
- Optional embedded video analytics for rapidly detecting important activity
- Up to 28 Mbps capacity, with superior image quality, optimized bandwidth utilization, and failover for high availability
- Connect up to 24 transmitters per access point, reducing equipment and installation costs
- Enhanced security via SSL-based authentication and AES with rotating 128-bit key

The Nextiva S4300 access point aggregates traffic from Nextiva S4200 wireless video transmitters and is ideal for outdoor, point-to-multipoint applications. The S4300 transmits video over the license-free 2.4 or 5 GHz wireless band or the licensed 4.9 GHz US or Canada public safety band. A built-in, multi-band antenna lets users switch wireless frequencies by reconfiguring the software, rather than replacing the entire unit.

### Built for Security and Performance

With Verint's state-of-the-art wireless technology and a compact, weatherproof enclosure, users can cost effectively deploy the S4300 wherever it is needed — from parking lots and perimeters to city-wide implementations and waterways.

The S4300 is built to deliver excellent performance. When using the unique Verint SPCF protocol, the S4300 features effective throughput of up to 28Mbps, more than 2½ times the capacity of prior devices. Additionally, up to 24 Nextiva S4200 wireless transmitters can be connected to a single S4300 access point.

The Verint SPCF/SDCF polling protocol resolves hidden node and quality of service issues that often arise with conventional Wi-Fi 802.11 products, with no degradation in video signal quality over extended range transmissions. SSL-based authentication helps secure configuration access, and AES encryption with rotating 128-bit key protects wireless transmissions from unauthorized interception. Additionally, the Verint SPCF proprietary protocol makes it possible to configure the master S4300 to take over when a nearby S4300 fails. This failover mechanism increases system reliability and availability, reduces the opportunity for critical image loss, and provides an excellent alternative to mesh wireless networks.

### Easy to Install, Configure, Update, and Manage

The Nextiva S4300 is equipped with built-in wireless site survey tools to facilitate installation and optimize configuration. A Power over Ethernet (PoE) injector reduces the number of cables needed for system connections, simplifying installation. Plus, users can remotely configure the S4300 and upgrade the firmware from any node on the network.

The Nextiva S4300 is fully integrated with the Nextiva video solution portfolio, including Nextiva Control Center, for centralized configuration and administration, and Nextiva HealthCheck, for automatic device health monitoring, diagnostics, and problem notification. Nextiva video management software helps increase system uptime and reduce cost of ownership, administration, and operation. Nextiva wireless video solutions lead the industry in innovation and value.



VIDEO INTELLIGENCE SOLUTIONS™

# Technical Specifications

## Network

- RF Interface
- Frequencies

Nextiva SPCF/SDCF 802.11a/802.11g PHY with proprietary MAC protocol  
2.40-2.4835 GHz (ISM)  
4.940-4.990 GHz (Public safety band US and Canada)  
5.250-5.350 GHz (U-NII-2) Not available in US & Canada  
5.470-5.725 GHz (DFS) Not available in US & Canada  
5.725-5.825 GHz (U-NII-3/ISM)

- Modulation
- Maximum Output Power
- Range (RF Line of Sight)

OFDM (Adaptive): BPSK, QPSK, 16QAM, 64QAM)  
2.4 GHz: 13 dBm 4.9 GHz: 20 dBm 5.x GHz: 23 dBm  
2.40-2.4835 GHz (8.5 dBi): up to 2.1 miles (3.4 km)  
4.940-4.990 GHz (12 dBi): up to 2.4 miles (3.9 km)  
4.940-4.990 GHz (18 dBi): up to 8.2 miles (13.2 km)  
5.250GHz-5.350GHz (12 dBi): up to 1.8 miles (2.9 km)  
5.470-5.725GHz (12 dBi): up to 1.7 miles (2.7 km)  
5.725-5.825 GHz (12 dBi): up to 2.1 miles (3.4 km)  
5.725-5.825 GHz (19 dBi): up to 6.2 miles (10.0 km)

- Data Rate (Max Burst Rate)
- Channels

6, 9, 12, 18, 24, 36, 48, and 54 Mbps  
2.4 GHz: 11, 3 non-interfering  
4.9 GHz: 2, 4, or 10 depending on user-configurable channel width, non-interfering  
5.3 GHz: 4, non-interfering  
5.4 GHz: 11, non-interfering (DFS)  
5.8 GHz: 5, non-interfering

- Encryption
- Protocols

128-bit AES with auto-key rotation  
RTP/IP, UDP/IP, TCP/IP, or multicast IP  
DNS and DHCP client

- Security
- Antenna Connector
- Ethernet Connector

SSL-based authentication  
SMA female  
Weatherproof 10/100Base-T (RJ-45)

## Internal Antenna Specifications

- Frequency Supported
- 3dB Horizontal Beamwidth
- 3dB Vertical Beamwidth

2.4 GHz (8.5 dBi); 4.9–5.8 GHz (12 dBi)  
67°; 38°  
56°; 30°

## Serial Port

- Interface Standard
- Operating Mode

RS-422/485  
Transparent (supports any asynchronous PTZ serial protocol)

## Power

- Input Voltage
- Maximum Consumption
- Connector

48V DC Power over Ethernet (PoE) 802.3af compliance  
PoE Class 3 (6.49 to 12.95W)  
Weatherproof circular

## Physical

- Enclosure
- Size
- Weight
- Environmental
- Humidity

NEMA 4X/IP 66 powder coat painted die-cast aluminum with wall-mount brackets  
8.75L x 3.5W x 5.5H in. (222L x 89W x 140H mm)  
4.6 lbs (2.1 kg) including mounting brackets  
-22°F to 122°F (-30°C to 50°C)  
100% at 122°F (50°C)

## Management

- Configuration
- Firmware Upgrade

Remote: via Verint Nextiva, SConfigurator, Internet Explorer, Telnet  
Local: via Internet Explorer or the Ethernet port using SConfigurator  
Via the Ethernet port of the network

## Models and Options

- S4300-PoE
- S4300-PoE-49
- S4300-PoE-CE
- S4300-PoE-UK

Outdoor 2.4/5.x GHz wireless access point with PoE injector, 82-foot (25-meter) outdoor Ethernet cable, multi-band antenna, and wall-mount and pole-mount brackets  
Public safety outdoor 2.4/4.9/5.x GHz wireless access point with PoE injector, 82-foot (25-meter) outdoor Ethernet cable, multi-band antenna, and wall-mount and pole-mount brackets  
European outdoor 2.4/5.x GHz wireless access point with PoE injector, 82-foot (25-meter) outdoor Ethernet cable, multi-band antenna, and wall-mount and pole-mount brackets  
United Kingdom outdoor 2.4/5.x GHz wireless access point with PoE injector, 82-foot (25-meter) outdoor Ethernet cable, multi-band antenna, and wall-mount and pole-mount brackets

Additional contry-specific models available, contact your Verint representative for details.

## Certification and Regulation

For information, please visit [www.verint.com/S4300](http://www.verint.com/S4300).

## Warranty

2-year limited warranty covering parts and labor (for the Americas). Contact your Verint representative for warranty details for other regions.

## About Verint Video Intelligence Solutions

Verint® Video Intelligence Solutions is the worldwide leader in networked video, a “single source” for virtually every facet of video surveillance operations: from cameras, encoders, and intelligent DVRs to video management, viewing, and analytics software.

## Verint. Powering Actionable Intelligence.®

Verint Systems Inc. is a global leader in Actionable Intelligence® solutions and value-added services. More than 10,000 organizations in over 150 countries use our workforce optimization and security intelligence solutions to improve enterprise performance and make the world a safer place. For more information, visit [www.verint.com](http://www.verint.com).



[videoinfo@verint.com](mailto:videoinfo@verint.com)  
1-866-NEXTIVA

330 South Service Road  
Melville, NY 11747 USA

[www.verint.com/videosolutions](http://www.verint.com/videosolutions)

Unauthorized use, duplication, or modification of this document in whole or in part without the written consent of Verint Systems Inc. is strictly prohibited.

By providing this document, Verint Systems Inc. is not making any representations regarding the correctness or completeness of its contents and reserves the right to alter this document at any time without notice.

Features listed in this document are subject to change. Please contact Verint for current product features and specifications. All marks referenced herein with the ® or TM symbol are registered trademarks or trademarks of Verint Systems Inc. or its subsidiaries. All rights reserved. All other marks are trademarks of their respective owners.

© 2010 Verint Systems Inc.  
All Rights Reserved Worldwide.

January 2011