
SUPER HIGH RESOLUTION WDR, TDN, MINI PTZ DOME WITH ENVIRONMENTAL HOUSING

VANDAL DOME CAMERA WITH ENVIRONMENTAL HOUSING

SDMV22DWH



- ► 1/4" Type EXview HAD CCD
- ► True Day/Night Mode: Color Converts to B/W in Low Light with an ICR (Infrared Cut Filter Removal)
- Perfect Image with Powerful Wide Dynamic Range in any Light
- ► Pan: 360° Endless, Tilt: 0°~180° (Digital Flip)
- 22X Optical Zoom / 16X Digital Zoom
- Auto Recognize Pelco P and Pelco D Protocols
- Define up to 120 Preset Camera Views that can be Recalled with a Simple Keyboard Command
- Up to 4 Tours, consisting of Presets, Patterns, Auto-Scans and other Tours, can be Programmed with over 150 Functions and Preset Locations
- Auto-Scans with Normal, Vector and Random Mode and Endless Auto-Pan with 13 Speed Steps
- Activate any of the 120 Presets from an External Alarm Input
- Incorporate up to 255 Domes in a Single System
- Environmental Housing Includes Heater, Blower and Sunshield
- Pendant and Wall Mount Options Available



VANDAL DOME CAMERA WITH ENVIRONMENTAL HOUSING


SDMV22DWH


PERFORMANCE SERIES

SPECIFICATIONS

	MODEL	SDMV22DWH
	Power Source	24VAC +- 10%
	Power Consumption	45W
Р	Image Sensor	1/4" Type EXview HAD CCD
	Total Pixels	811(H) X 508(V)
	Scanning System	2:1 Interlace
0	Scanning Frequency	15.734KHz(H), 59.94Hz(V)
W	Sync. System	Internal / Line Lock
Е	Resolution	580TVL (Color), 630TVL (B/W)
R	Min. illumination	0.5 lux (Color), 0.01 lux (B/W), 0.001 lux (Low-Shutter)
	Video Output	1.0 Vp-p (75 ohm, Composite)
	S/N Ratio	> 50dB (AGC off)
	Camera Control	RS485 (Fastrax II, Fastrax IIe, Pelco D, Pelco P)
	TRUE Day/Night	Yes
F	WDR	Yes
U	Motion Detection	Yes (in Preset)
N	Panning Angle	360° Continuous Rotation
C	Tilting Angle	0° ~ 180° (Digital Flip: On / Off)
T	Preset Speed	Pan/Tilt: 380°/sec.
	Preset	120 Position
	Tour	4 Tours (Consist of 42 Functions / 1 Tour)
0	Auto Scan	1 Auto Pan and 4 Auto Scans Capability
Ν	Area Title	8 Areas w/12 Characters
S	Alarm Input	Off / NC / NO (1 Channel)
	Alarm Output	1 Channel (TTL)
L	Zoom Ratio	Optical x22, Digital x16 Zoom (Video AF)
N	Focus Length	f = 3.9mm ~ 85.8mm
S	Aperature Ratio	F1.6 (wide) ~ F3.7 (tele)
С	Power Input	2-Pin Terminal Block
0	Video Output	BNC Connector
Ν	RS485 Control	2-Pin Terminal Block
N	Alarm Input/Output	4-Pin Terminal Black
E	Operating Temperature	-22°F ~ 122°F (-30°C ~ +50°C)
С	Operating Humidity	0 ~ 90% RH (Non-condencing)
T	Storage Temperature	-4°F ~ 140°F (-20°C ~ 60°C)
O R	Dimensions (Dia x H)	7.32 x 8.07in (186 x 205mm)
H	Weight	4.85lbs (2.2kg)
	Conformity Certifications	FCC, UL, RoHS

DIMENSIONS 125.5 Dip Switch Cover Ø110 Ø186





ACCESSORIES

DB241 Pendant Mount DB242 Wall Mount PM304 Parapet/Roof Mount

Keyboard Controller; LCD Monitor SCD5LCDN

Keyboard Controller SCK162J **Corner Mount** A-CM150 Pole Mount A-CM151

Wall Mount / Power Supply Combo PB120





A-CM151







SDC5LCDN

SDK162J

