



SF337C Emergency Shower Switch Specification Sheet

IL629
Section E
Rev. 11 - 03/2011



SF337C Emergency Shower Switch
(Cord Not Shown)

ARCHITECTS' AND ENGINEERS' SPECIFICATION

The emergency shower switch shall be TekTone® SF337C or approved equal. Operation of emergency signals shall be accomplished by a short pull on the washable TPU plastic cord or by pulling down on the RED lever marked **EMERGENCY**.

The red **CALL-PLACED** indicator shall flash to assure the patient that the call has been placed.

The emergency shower switch shall be waterproof if mounted according to manufacturer's instructions. If mounted correctly, the faceplate shall be sealed from the electronic components. The switching mechanism shall consist of a reliable reed switch with a sealed magnet actuator.

The SF337C shall be UL® 1069 Listed.

FEATURES

The SF337C Emergency Shower Switch is for any location where activation of an emergency signal is required. The design is such that it may be located anywhere in a shower, bath or tub room, regardless of environmental conditions. The combination of rubber-grommetted mounting screws, rubber mounting gasket, and completely sealed front faceplate make it waterproof (if properly installed). Electronic components are mounted on a circuit board, including an industry-proven reliable reed switch for circuit initiation. The activating magnet is mounted on the large pull-down lever, which is completely sealed in plastic. The indicator LED is also completely sealed.

Due to the flexibility of its design, the SF337C may be used as a pull cord or as a pull down activated emergency switch. The pull cord supplied may be used for emergency call activation, or if desired, the large 1.1" (28 mm) red pull-down lever may be used. Dome light and system annunciation vary according to the manner in which the SF337C is connected.

- UL® 1069 Listed
- Waterproof if installed per manufacturer's instructions
- Call-placed indicator
- Call cancel at point of origin
- Attractive, flame-retardant (UL® 94V-0) plastic faceplate
- 1.1" (28mm) wide pull-down lever
- Washable TPU plastic pull cord kit is included

SPECIFICATIONS

Dimensions:	Height:	4.5"	(114mm)
	Width:	2.8125"	(72 mm)
	Depth:	1.625"	(41 mm)
	Projects:	0.6875"	(17 mm)
(including pull down lever)			
Construction:	Flame-retardant (UL® 94V-0) plastic		
Connections:	Plug-in type.		
Housing:	Single gang ring with square box.		

APPLICABLE SYSTEMS

Tek-CARE® 400 P5 Nurse Call System
Tek-CARE® NC300 II Nurse Call System
Tek-CARE® NC200, NC150, NC110 Nurse Call Systems
Tek-CARE® 500 Wireless Emergency Call System

www.tektone.com

277 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.net
Phone: (828) 524-9967 • Fax: (828) 524-9968 • Tech Support: Choose option 2 • Sales: Choose option 3
TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)