



## Product Specification Sheet



APS739

Rev. 1 - 05/2010



**Szena COLOR Video-Intercom  
Monitor (shown in White)**

### ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The open-voice (loudspeaking) color video-intercom monitor station(s) shall be Alpha Communications®/Golmar Szena series, or approved equal. Monitor(s) shall be mounted surface (or flush using optional model CE-SZENA flush back box). Monitor(s) shall be connected using looped 'common' wires and shall not require any selective (point) wires or coaxial cabling. Monitor(s) shall include a high quality 3.5" color LCD screen. Monitors using mirrors or other non-flat type screens, or coaxial cable shall not be acceptable. Monitor(s) shall feature electret condenser microphone for exceptional voice fidelity. Monitor shall include a door release button with Key symbol, and additional auxiliary switches for features such as brightness/contrast, etc. Monitor shall feature an electronic chime signal, with a 2nd chime sound for optional private door bell signaling. Monitor shall be in White (or optional Black, Aluminum or Dark Gold as specified by architect or building owner) and shall only protrude from the wall 1.40" inches (36mm).

Contractor shall observe all local and national electrical and building codes.

Copyright© 2010, Alpha Communications®, All Rights Reserved

### Szena Series COLOR Video-Intercom Monitors

The AlphaCommunications®/Golmar Szena series open-voice (loudspeaking) color monitors are designed to meet virtually any requirement for video-intercom security, while not requiring any riser coaxial cabling, or any selective (home-run) wiring.

These attractive monitors are conveniently surface mounted right on the wall. Monitors can be changed to flush mount with the addition of an optional model CE-SZENA flush back box.

All Szena series monitors feature a crystal clear 3.5" color LCD flat screen monitor (measured diagonally), electronic chime signaling, one (1) momentary door release button switch (with key symbol), and switches for additional functions.

### FEATURES

- 3.5" (diagonal) Crystal Clear Color LCD video screen
- No riser coaxial cabling required - uses looped wiring
- Convenient Half-Duplex Voice Operation
- Easy Installation (surface or optional flush)
- Clear Voice Fidelity using Electret Condenser Microphones
- Rugged and Reliable. Simple to Operate
- Low profile surface monitor protrudes only 1.40" from wall
- Available in 3 optional extra cost finishes, Black, Alum. and Dark Gold (White standard)
- Blue backlighted soft keypad
- Casing manufactured in polished ABS Black plastic

### SPECIFICATIONS

**Dimensions:** All **Szena** series monitors are 3.82"W (98mm) x 8.15"H (208mm) x 1.40"D (36mm). All dimensions shown are outside dimensions for the surface type monitor.

**Flush Housing:** **Model CE-SZENA.** Use in addition to the monitor unit. **OPTIONAL.**

**Mounting Plate:** **Model RC-SZENA** Allows the monitor to mount to the finished wall surface, and has the connecting electronics. One (1) required for each Szena monitor.

*Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.*