



N450 Wireless Gigabit Router

TEW-691GR(1.0R)

TRENDnet's N450 Wireless Gigabit Router, model TEW-691GR, redefines wireless router performance. This router's raw horsepower seamlessly streams HD movies to your entertainment center, transfers content from countless users, and generates record wireless coverage.

Gigabit Wide Area Network and Local Area Network ports transfer wired data fast. Embedded GREENnet technology reduce power consumption.

Advanced Multiple Input Multiple Output (MIMO) antenna technology with three spatial streams per antenna generates a maximum theoretical wireless throughput of 450Mbps. Wi-Fi Protected Setup (WPS) integrates other WPS supported wireless adapters at the touch of a button. The latest in wireless encryption and a secure firewall protect your digital network. WMM® Quality of Service (QoS) technology prioritizes gaming, Internet calls, and video streams. LEDs on the front of the router convey device status.

Features

- High-speed data rates of up to 450Mbps using an IEEE 802.11n connection
- IEEE 802.11n/b/g compliant
- 4 x 10/100/1000Mbps Auto-MDIX LAN ports
- 1 x 10/100/1000Mbps WAN port (Internet)
- On/off power switch
- On/off wireless network switch
- 1 x Wi-Fi Protected Setup (WPS) button
- One touch wireless connection using the WPS button
- Embedded energy saving GREENnet technology
- Compatible with most popular cable/DSL Internet Service Providers using Dynamic/Static IP, PPPoE, L2TP, and PPTP connection
- Advanced firewall protection with Network Address Translation (NAT) and Stateful Packet Inspection (SPI)
- Access restriction with Internet Access Control: MAC, Protocol, and Domain filtering
- Virtual server and Application Level Gateway (ALG) services for special Internet applications
- Universal Plug and Play (UPnP) for auto discovery and support for device configuration of Internet applications like RTP/RTSP, SIP, FTP, TFTP, NTP, and SMTP
- Multiple pass-through sessions for popular VPN applications (IPSec, L2TP, and PPTP)
- Advanced QoS support includes: Uplink speed control, IP prioritization, and Wi-Fi Multimedia (WMM)
- Complete wireless security with WPA/WPA2-RADIUS, WPA/WPA2-PSK, and WEP
- 3-year limited warranty

*Maximum wireless signal rates are referenced from IEEE 802.11 theoretical specifications. Actual data throughput and coverage will vary depending on interference, network traffic, building materials and other conditions.

N450 Wireless Gigabit Router

TEW-691GR(1.0R)

SPECIFICATIONS

Hardware	
Standards	- Wired: IEEE 802.3 (10Base-T), IEEE 802.3u (100Base-TX), IEEE 802.3ab (1000Base-T) - Wireless: IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
LAN	4 x 10/100/1000Mbps Auto-MDIX port
WAN	1 x 10/100/1000Mbps Auto-MDIX port
WPS Button	Wi-Fi Protected Setup (WPS) connects with other WPS compliant devices
WDS	Enable/disable Wireless Distribution System support
LED Indicator	Power, WLAN, LAN, WPS
Power Adapter	12V DC, 1A external power adapter
Power Consumption	450mA (max.)
Dimension (L x W x H)	148x 180 x 32mm (6.2 x 7.1 x 1.0in.)
Weight	289g (10 oz)
Temperature	Operation: 0°~ 40°C (32°F~104°F) • Storage: -20°~ 60°C (- 4°F~140°F)
Humidity	Max. 90% (non-condensing)
Certifications	CE, FCC
Wireless	
Frequency	2.412 ~ 2.472 (..84??)GHz
Antenna	3 x 4dBi fixed dipole antennas
Modulation	OFDM: BPSK, QPSK, 16-QAM, 64-QAM, DBPSK, DQPSK, CCK
Data Rate	802.11b: up to 11Mbps • 802.11g: up to 54Mbps • 802.11n: up to 450Mbps
Security	64/128-bit WEP, WPA/WPA2-PSK, WPA/WPA2-RADIUS, Multiple SSID
Access Control	MAC Address Filter (Up to 24 entries)
Output Power	802.11b: 11dBm (typical) • 802.11g: 15dBm (typical) • 802.11n: 15dBm (typical)
Receiving Sensitivity	802.11b: -84dBm (typical) • 802.11g: -72dBm (typical) • 802.11n: -69dBm (typical)
Channels	2.4GHz : 1~11 (FCC), 1~13 (ETSI)

NETWORKING SOLUTIONS



PACKAGE CONTENTS

- TEW-691GR
- Multi-Language Quick Installation Guide
- CD-ROM (User's Guide)
- Cat. 5 Ethernet cable (1m / 3.2ft)
- Power adapter (12V, 1A)

RELATED PRODUCTS

TEW-624UB	300Mbps Wireless N USB Adapter
TEW-623PI	54Mbps Wireless G PCI Adapter
TEW-654TR	300Mbps Wireless N Travel Router Kit

CONTACT INFORMATION

TRENDnet®

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500

Fax: 1-310-961-5511

Web: www.trendnet.com

Email: sales@trendnet.com

1-888-326-6061

