



The Perfect Experience

<http://pro.jvc.com>

CCTV Color Camera Line-Up

NTSC
2008

Mini Dome Camera				Box Type Camera					
TK-C215V4U	TK-C215V12U	TK-C215VP4U	TK-C215VP12U	TK-C750U	TK-C920BU	TK-C925U	TK-C1530U	TK-WD310U	
									
1/4 CCD				1/3 CCD					
380,000 pixels				250,000 pixels	380,000 pixels				
50 dB (AGC off)				50 dB (AGC off)					
540 TVL				330 TVL	550 TVL	540 TVL	540 TVL	480 TVL	
INT/Line lock				INT/Line lock	INT/Line lock	INT/Line lock	INT/Line lock		
0.75 lx	1.0 lx	0.8 lx	1.1 lx	0.28 lx	0.35 lx	0.4 lx	0.4 lx	0.9 lx	
0.4 lx	0.6 lx	0.4 lx	0.6 lx	—	0.25 lx	0.05 lx	0.05 lx	0.25 lx	
DC iris				DC iris	Video iris/DC iris	Video iris/DC iris	Video iris/DC iris	Video iris/DC iris	
Auto/Manual				Auto/Manual	Auto/Manual	Auto (Wide/Narrow) /Manual		Auto/Manual	
—				Yes					—
Yes				Yes					—
Yes (max. 26 dB)				Yes (max. 26 dB)					Yes (max. 34 dB)
Easy D/N				—	Easy D/N	IR on/off		Easy D/N	
—				—					Yes
2.8 - 10 mm	3.8 - 45.6 mm	2.8 - 10 mm	3.8 - 45.6 mm	(Delivered without lens)					
F1.3	F1.6	F1.3	F1.6						
24 VAC /12 VDC				24 VAC /12 VDC					
1.2 W	6.6 W	4.2 W	6.6 W	3.3 W	4.7 W	4.8 W	5.0 W	5.7 W	
1.43 lbs. (650 g)	1.54 lbs. (700 g)	2.46 lbs. (1.2 kg)	2.86 lbs. (1.3 kg)	1.75 lbs. (300 g)	0.82 lbs. (370 g)	0.88 lbs. (480 g)	0.88 lbs. (480 g)	0.73 lbs (330 g)	
ø 6-1/4 inches H 4-7/8 inches		ø 6-3/8 inches H 5 inches		W 2 inches H 2-3/8 inches D 5 inches		W 2-5/8 inches H 2-1/4 inches D 5 inches	W 2-1/2 inches H 2-3/8 inches D 5 inches	W 2 inches H 2-3/8 inches D 4-1/4 inches	
—	—	IP66	IP66	—					
14 °F to 122 °F				14 °F to 122 °F					
• Triple axis rotation		• Vandal resistant • Triple axis rotation • Easy installation					• External controll interface • Privacy masking		
						• White balance can be adjusted automatically under a wide variety of light source • CRT/LCD Settings			
\$360	\$519	\$579	\$729	\$169	\$265	\$332	\$495	\$599	