TLTM19AD

TRIVIEW° **LCD Touch Monitor**



- · 19" Touch Screen
- 5 Wire Resistive
- USB & RS-232 Interface
- Audio
- · Multi Language OSD
- · Rack Mountable
- VESA Mount 100 x 100m²
- · Includes Desk Stand w/ adjustable angle



LCD Panel

Screen Size 19" (5:4)

Viewable Size 14.81" (H) x 11.85" (V) Dot Pitch 0.294mm x 0.294mm

View Angle H/V 170° / 160° **Contrast Ratio** 1000:1 Brightness 300 cd/m^2 Resolution 1280 x 1024

Response Time 5ms **Display Color** 16.7M

Power Supply

Input Voltage 100~240VAC / Monitor:

12VDC / 4.16A

Consumption 33W max.

PC In Analog & Digital

Input VGA D-sub 15 pin;

Analog RGB: 0.707Vp-p /

75Ω

Support Timing VESA VGA / SVGA / XGA /

SXGA

Audio

Input Connector: 1 x stereo

iack.

Level: 1.0Vp-p / 1 KHz

Speaker 1W x 2 embedded

Touch Panel

Touch Screen 5 Wire Resistive Type **Touch Controller** USB & RS-232 Interface

Mechanical

Dimension 16.5" x 14.1" x 3.7"

10.5 lbs Weight







