

V2216 Series

Network Video Management Software

Infinova
The Integrator's Manufacturer

Features

System


- Multiple systems cascading, building a central management platform to large network video system
- Support CMS hot standby, NVR redundancy and SMT multicast functions
- Major and minor code streams auto switch according to image size, so as to reduce client CPU resource consumption and improve efficiency
- Support digital matrix functions, such as configuration of TOUR, SALVO and Event Timer
- Support device video loss alarm and NVR hard disk (HD) error / HD expiration alarm
- Support remote restarting to system devices and servers
- Support searching alarm information based on preset conditions, searching in a time period, and calling alarm video via the searching results
- Support audio broadcasting for multiple IP front-ends
- Support analog keyboard
- Support clients to customize functions

Services input

- Support third party alarm devices: BOSCH, Honeywell, INANTER etc.
- Support third party access control integration: DDS access control, Lenel access control, PEAK access control etc.
- Support transmit the operating order of V2216 software to third party alarm devices
- compatible with all series DVR, encoder, and camera of Dahua and Hikvision
- Integrates with analog surveillance system seamlessly to realize mutual live video calling between digital and analog systems
- Supply with SDK, and support DB33, GB/T 28181 platform input, RTSP input, ONVIF1.0/2.0 input

Client and TV wall

- Support multilevel E-maps, and can remember the size and position of the video window pop-out from the E-maps
- Support linked layers and Hawkeye function of E-map
- Support real time video viewing picture in picture function
- Optimize decoding performance and configure separated dual channel display card, allowing to view 8*1080P high definition video
- Support screen vector PTZ control and intelligent operation like zooming in the selected zone and central position adjustment by mouse click
- Support light, wiper and user-defined control function
- Supply with analog TV wall operations, switch videos by mouse dragging
- Support multiple camera screen stitching
- Support keyboard to switch screen



Description

The Infinova's V2216 network video management software is a central management platform for all kinds of network video systems. It includes two versions: V2216 Professional and V2216 Enterprise. The former is suitable for medium surveillance installation and supports a maximum of 128 video inputs, while the latter is the most powerful software which suitable for any large surveillance installation.

The V2216 digital matrix functions inherit major advantages from classic Infinova video matrix switchers, such as system tour, salvo, and alarm management. And the software allows network keyboard to control the system. The operation of V2216 is easy and convenient as that of analog video matrix. Thanks to compatibility with all Infinova digital video products and integration with all Infinova series matrix switchers and Pelco matrix switchers, the V2216 platform can perform centralized management and control over the digital video system and analog video system.

The V2216 system provides TV Wall mode. The video play window on client monitor can be used as TV wall, and the IP camera's video can be switched to the TV wall via physical keyboard or virtual keyboard. This will save the cost of decoding devices while retaining the convenience of digital matrix switching system, providing intelligent, flexible, quick and convenient services to users.

Intelligence (optional)

- Support intelligent analysis of real time video and record video with the function of counting, transgression, loitering, track, item left/ loss, inspection on exit and entrance
- Support the quality inspection of real time video and record video with the function of video occlusion and loss, definition abnormal, offset, brightness abnormal, color cast, noise interference, video screen freeze

Ordering Information

V2216 PROFESSIONAL

V2216 Professional supports up to 128 video inputs

Ordering Information

V2216-P	V2216 Professional version, supports up to 128 video inputs
V2216-P-M	V2216-P maintenance plan
V2216-P-C1	V2216 Professional License, for 1 video input
V2216-P-C1-M	V2216-P-C1 maintenance plan

V2216 ENTERPRISE

V2216 Enterprise supports up to 9999 video inputs.

Ordering Information

V2216-E	V2216 Enterprise version, supports up to 9999 video inputs
V2216-E-M	V2216-E maintenance plan
V2216-E-C1	V2216 Enterprise License, for 1 video input
V2216-E-C1-M	V2216-E-C1 maintenance plan

Optional Accessories

Hardware:

V2216-R400A	Network Video Management Server
V2216-R400W	Network Video Management Server, attached with Windows Server 2008 SP2 operating system

Note:

As the server of SMT and NVR, V2216-R400 supports to store 45 8M codes stream, 60 6M code stream, 80 4M codes streams and 128 2M when it transmit sync multiple video to LMC, and the disk is full and with overwriting 32 original files and with 16 video playbacks

Software:

V2216-IVS	intelligent video analysis server
V2216-IVS-C1	V2216 intelligent video analysis License, for 1 channel

Note: V2216-IVS is able to be configured by V2216-P and V2216-E.

System Requirements

Recommended PC Configuration for Clients (LMC / NCT)

CPU	Intel®Core™ i7-2600 CPU @3.40GHz,3.40GHz
Nominal CPU Frequency	≥ 2.83 GHz
Memory	≥ 4G
Network Adapter	1000Mbps, Ethernet
Display Card	≥ 256M (display memory)
Operating System	Windows XP / 7, supports Chinese, English and Traditional Chinese versions

Recommended PC Configuration for Servers of CMS/SMT/NVR (Professional Version)

Nominal CPU Frequency	≥ 2.4GHz
Memory	4G
Network Adapter	≥2000Mbps, Ethernet
Operating System:	Windows 2003 Server / 2008 Server, supports Chinese, English and Traditional Chinese versions

Recommended PC Configuration for Servers of CMS/SMT/NVR (Enterprise Version)

CMS

Nominal CPU Frequency	≥ 2.1 GHz
Memory	2G
Network Adapter	1000Mbps, Ethernet
Operating System:	Windows 2003 Server / 2008 Server, supports Chinese, English and Traditional Chinese versions

SMT/NVR

Nominal CPU Frequency	≥ 2.4GHz
Memory	4G
Network Adapter	≥2000Mbps, Ethernet
Operating System:	Windows 2003 Server / 2008 Server, supports Chinese, English and Traditional Chinese versions

Note: It is strongly recommended to install CMS in a separate server, and then install SMT and NVR in the same server. Multiple suits of SMT/NVR can be installed if there are many surveillance sites.

Typical System Application Diagram

