



High Resolution B/W Weatherproof Camera with Sunshield



Features	Benefits
Weatherproof	. Use indoors or outdoors
Snap-on Sunshield	Eliminates glare from the sun or strong sources of light
Universal Mounting System	. Mount on wall, ceiling or parapet
Electronic Shutter	Perfect pictures in all lighting conditions

Resolution	. 420 lines
Minimum Illumination	.0.02 lux
Image Device	. 1/3" B/W CCD image sensor
Electronic Shutter	. 1/60 - 1/100,000 seconds
Lens	.3.6mm wide angle lens
Lens Options	
Video Output Level	
Video S/N Ratio	. Greater than 48 dB
Outputs	. Video- BNC, Power- DC jack
Number of Pixels	.512 H x 492 V
Scanning System	.EIA standard 525 line 60 fields/second
Scanning Frequency	. 15.75 kHz horizontal 60 Hz vertical
Operating Temperature	14°F to 120°F
Humidity	. Within 95% RH
Power Consumption	. 100 mA
Power Supply	
6 . W .	(UL and CSA listed)
Camera Mount	
Housing	. Black metal, with removable sunshield
Dimensions	.2.37"L x 1.07"W x 1"H
Weight	. 2.2 oz

Package Includes:	
VL-128RS Camera 12V DC Regulated Power Supply	Installation Instructions Universal Mounting Bracket
Mounting Screws	G

Specifications subject to change