



VL647iLT 2.8 - 12mm DC auto iris varifocal lens

Features


- 580 TV lines
- 0.00001 lux (Intense Light @ 256x)
- Day & night camera without using IR LEDs
- Featuring HLC for enhanced backlight operation
- Digital image stabilization
- Advanced noise reduction circuitry eliminates blur
- Weather/tamper resistant dome (IP67 rating)
- Chameleon™ Cover - snaps on and can be painted to match any décor!
- 5 year warranty

Specifications

Image Sensor	1/3" Sony Super-HAD II™ CCD
Resolution	580 TV lines
Minimum Illumination	0.00001 lux (intense light x256)
Total Pixels	811 (H) x 508 (V)
Effective Pixels	768 (H) x 494 (V)
Scanning System	2:1 interlace
Synchronization	Internal
OSD	Available
Backlight Compensation	SLC / HLC / Off
S/N (Y signal)	52dB (AGC Off, Weight On)
White Balance	ATW / AWB / AWC - Set / Manual / Indoor / Outdoor
Electronic Shutter Speed	Auto: (1/50 sec. 1/60 sec. - 1/100,000 sec.)
Intense-LT	Off / Auto (selectable limit x2 - x256)
Gain Control	High / Middle / Low / Off
S-DNR	On / Off (0 - 100 level adjustable)
S-WDR	Indoor / Outdoor / Off



Camera shown with snap-on
Chameleon™ Cover



Motion Detection	On / Off (4 zone)
Privacy	On / Off (8 zone)
Mirror	Off / Mirror / V-Flip / Rotate
Freeze	On / Off
Sharpness	0 - 31' (level adjustable)
Day & Night	Color / BW / Auto
Digital Zoom	On (32x) / Off
Power Supply	12VDC (power supply not included)
Power Consumption	200mA
Operating Temperature/	
Humidity	14° F - 122° F / RH 95% max.
Storage Temperature	- 4° F - 140° F / RH 95% max
Dimensions	3.23" (H) x 4.33" (D)
Weight	1.54 lbs.

Optional Accessory



PSW5
Power Supply



Speco Technologies is constantly developing and improving products.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 1/27/12

For more information contact Speco Technologies

200 New Highway, Amityville, NY 11701 • Toll Free: 1-800-645-5516 • Fax: 631-957-9142 or 631-957-3880
www.specotech.com