




CHRONO-X

8 & 16 Channel Real Time D1 Digital Video Recorders

The CHRONO-X 8 and 16 channel DVRs are state-of-the-art Full-Featured Ultra Powerful DVRs with the latest H.264 compression with built-in data redundancy and direct connect Multi-Channel POS. With an HDMI 1920x1080 Resolution output and up to 480fps of recording and playback in full frame D1 resolution, it's easy to see why the Chrono is the choice of the most demanding professionals. The system Setup Wizard and User Friendly GUI make this an easy product to install and users are able to upload and download multiple settings to a thumb drive for ease of future installation. Available with up to 6TB internal storage and shipped complete with IR Remote control and rack mount ears. Included Client/CMS Software and free I Phone, I Pad and Android apps enable unlimited remote monitoring options.

FEATURES:

- Highly efficient H.264 compression
- Built-in Data Redundancy
- Real-time D1 recording and playback
- HDMI Output with 1920x 1080 Resolution
- Remote Control of additional Chrono-X DVRs locally without the use of a remote PC
- System Setup Wizard and User Friendly GUI
- Multi-Resolution recording
- 4 Selectable Spot Outputs with Sequence and event Pop-up
- Built-in Point-of-Sales support for multiple registers or ATMs
- Web Client & CMS (Central Management Software) Included
- Free I Phone and Android Apps
- Built-in DVD-RW
- Two Way Audio with Individual Audio Input for each Video Input



Chrono Series Remote Viewing Apps for iPhone, iPad & Android



	VT-CX840	VT-CX1680
Video Input	8 Channels	16 Channels
IPS (Display / Recording)	240 / 240	480 / 480
Video Output	1 HDMI & 1 VGA - 1080P (1920 x 1080)	
BNC Output	Monitor: 1 Composite (BNC) / Spot: 4 Composite (BNC)	
Audio In/Out	8 Line In (RCA) / 1 Line Out (RCA)	16 Line In (RCA) / 1 Line Out (RCA)
Storage	Up to 3 Internal HDD (SATA) / Internal DVD-RW / E-SATA	
Archive	CD/DVD-RW / USB Device / Network / External HDD	
USB Port	1 Front	
System Control	Front Panel, USB Mouse, Joystick Controller, Included IR Remote Control	
Network	TCP/IP, HTTP, DHCP (DDNS), PPPoE, RTSP, RTP	
RJ-45 Ethernet Port	10M/100M/1Gbps	
Playback Rate	240 fps @ 704x480	480 fps @ 704x480
PTZ	1 - RS-485 - Supports most of PTZ protocols with up to 255 Presets	
Point of Sale (POS)	YES (Multi Input)	
Motion Area Setting	16 x 16 Grid Configuration & Multilevel Sensitivity per Channel	
Recording Resolution Setting	By each camera for different resolution setting(CIF/2CIF/D1)	
Recording Quality Control	4 Levels (Low/Standard/High/Highest)	
Player	Backup player, Windows Media Player and HDD PC Viewer	
E-mail notification	E-mails to specific users to notify events	
System Configuration	Full setup configuration over network	
Bandwidth limit	YES: Adjustable by User	
Two-Way Audio	YES	
Case Form Factor	2U	



VT-CX840 Rear Connections



VT-CX1680 Rear Connections