



Discreet surveillance made easy. These simple plug and play cameras allow for vertical adjustment to obtain the optimum viewing angle with ease. Comes standard with a 3.6mm wide angle lens. Optional lenses are also available ranging from 2.9mm to 25mm.

FEATURES

- Color CCD Image Sensor with 420 TV Lines (VT-SMKC1) / 550 TV Lines (VT-SMKC1/H)
- Minimum Illumination of 0.5 Lux
- Camera Mounted On Adjustable Gimbal To Achieve the Perfect Viewing Angle
- 3.6mm Standard lens Included (Optional 2.8mm to 25mm Available)
- Dimensions: 5.12" (OD) X 2.29" (H)

Detailed Specifications	VT-SMKC1	VT-SMKC1/H
Image Device	1/4" DSP Color Panasonic CCD Image Sensor	1/3" DSP Color Panasonic CCD Image Sensor
Effective Pixels	510 x 492	768 x 492
Resolution	420 TV Lines	550 TV Lines
Minimum Illumination	0.5 Lux	
S/N Ratio	More Than 48dB	
Electronic Shutter	1/60 to 1/100,000 sec.	
AGC	On	
Sync. Mode	Internal Sync.	
Scanning System	2:1 Interlace	
Gamma Correction	0.45	
Horizontal Sync. Frequency	15.734KHz	
Vertical Sync. Frequency	60Hz	
Video Output	Composite: 1.0 Vp-p / 75 Ohm	
Power Source	12VDC	
Power Consumption	120mA	300mA
Operation Temperature	-10° ~ 50°C (14° ~ 122°F) Less Than 80% RH	
Standard Lens	f3.6mm (Optional 2.8mm to 25mm Available)	
Dimensions (W x H)	5.12" x 2.29" (130 x 58mm)	
Weight	12.34 Oz. / 350 g. / 0.77 Lbs.	

