

VTC-IRV30/2810

Day/Night IR Bullet Camera
w/100' Range



FEATURES

- 1/3" Sony Super HAD II High Resolution Color CCD
- 550 TV Lines of Resolution
- 2.8~10mm / F1.2 Varifocal Auto Iris Lens
- 30 - 850nm IR LEDs with 100' Range
- 0 Lux Operation (IR LEDs On)
- IP-66 Rated Water Resistance
- Heavy Duty Mount with Cable Feed Through
- 12VDC/24VAC Dual Voltage Operation



(888) VITEK-70 | WWW.VITEKCCTV.COM
28492 Constellation Road Valencia, CA 91355

VTC-IRV30/2810

Day/Night IR Bullet Camera
w/100' Range

Detailed Specifications

Image Device	1/3" Sony SuperHAD II Color CCD
Effective Pixels	768 x 494 (NTSC) / 752 x 582 (PAL)
Resolution	550TVL (Day) / 600TVL (Night)
Sensitivity	0.05Lux(F1.2@40IRE), 0Lux with built-in 30 Infrared LEDs
S/N ratio	More than 50dB with AGC off at 50IRE
Electronic Iris	1/60 - 1/100,000sec (NTSC) 1/50 - 1/100,000sec (PAL)
White Balance	3,000°K - 8,000°K Automatic tracking
BLC	Built-in, Factory set to ON
Video Output	VBS 1.0Vpp +/-10%, 75ohm
Built-in Lens	1/3" Vari-Focal, f=2.8-10.0mm, F1.2, DC Auto Iris
Infrared LEDs	30pcs @ 850nm
IR Distance	35M (110')
Operation Power	24Vac(20~28.8Vac) or 12Vdc (11.5~30Vdc), 5Watts max
Cable length	5' (1.5M)
Operating Conditions	14 - 122 degrees F (-10°C - +50°C), 85% RH Max. (non-condensing)
Dimensions (Dia. x H)	2.68" x 8.66" (68mm x 220mm)
Net Weight	1.21 lbs (550g)