




May be Surface (Includes Surface Mount Casing) or Semi-Flush Mounted for Sleek, Low Profile Installation.



Secondary Video Output Enables Ease of Adjustment after Installation.



Friction Fit Ball Mount Camera Module Can Achieve Virtually Any Viewing Angle.

FEATURES

- High Resolution 480 or Super High Resolution 550 TV Line Cameras
- Flush or Surface Mount
- UTP Interface Option Available
- Dual Voltage 12VDC & 24VAC
- Infinity Ball Mount for Any Viewing Angle
- Lens options: 2.9-10mm, 9-22mm, or 18-50mm
- 1" Conduit Knockout
- Available in off white or black color

Available Configurations Include:

VTD-MH2910 / MH922 / MH1850

Indoor Color Dome Camera w/2.9-10mm, 9-22mm or 18-50mm Varifocal Lens & 480TVL

VTD-MX2910 / MX922 / MX1850

Indoor Color Dome Camera w/2.9-10mm, 9-22mm or 18-50mm Varifocal Lens & 550TVL



Detailed Specifications	VTD-MH2910 / MH922 / MH1580	VTD-MX2910 / MX922 / MX1850
Image Sensor	1/3 Sony New Structure Super HAD CCD	
Sync System	Internal	
Scanning system	2:1 Interlace	
Lens Options	2.9-10mm, 9-22mm or 18-50mm	
Horizontal Resolution	480 TV Lines	550 TV Lines
Min. Illumination	0.2Lux (F1.2@40IRE)	
S/N Ratio	More than 52dB AGC OFF at 50IRE	
Video Output	1.0Vp-p composite, 75 Ohms	
Effective Pixels	768(H) x 494(V)	
Electronic Shutter	1/60 ~ 1/100,000	
White Balance	2000~8000 K Automatic Tracking	
Operating Temperature	14°F ~ 122°F (-10°C ~ +50°C)	
Operating Humidity	Within 85% RH	
Power Consumption	3 Watts	
Power Requirement	12VDC/24VAC Dual Voltage (500 mA Minimum)	
Dimensions (H x Dia.)	4.45" x 5.71" (113mm x 145mm)	



VT-MDPLMT
Mighty Dome Pole
Mount



VT-MDCNMT
Mighty Dome Corner
Mount



VT-MD/CMT
Mighty Dome Ceiling
Mount



VT-MD/WMT
Mighty Dome Wall
Mount



VT-MD-2VOC
Cable for Secondary
Video Output

Dome Housing Dimensions

