

Overview



VertiLine16Di



Altronix VertiLine16Di CCTV Isolated Rack Mount Power Supply provides 16 PTC protected power outputs in a space saving 1U EIA 19" rack mount chassis which may be rack, wall or shelf mounted. This unit features individually selectable 24VAC and/or 28VAC power outputs with surge suppression.

VertiLine CCTV Isolated Rack Mount Power Supplies are also available in eight (8) output models.

Specifications

Input:

- Selectable 115VAC 60 Hz/230VAC 50/60 Hz input.
 - 115VAC 60 Hz., 7 amp.
 - 230VAC 50/60 Hz., 4 amp.

Output:

- Sixteen (16) individually selectable 24VAC or 28VAC power outputs with OFF position.
- 24VAC or 28VAC @ 16 amp max. total (1 amp per device, 2.5 amp max.).
- Individual electronically isolated outputs.
- Sixteen (16) PTC protected outputs rated @ 2.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 146-170 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement:
115VAC: 805VA, 230VAC: 920VA.

Mechanical:

- Units can be rack, wall or shelf mounted.
- Modular 1U standard EIA 19" rack mount chassis
- Enclosure Dimensions (H x W x D approx.):
1.625" (41.275mm) x 19.125" (486mm)
x 8.5" (216mm)
- Product weight (approx.): 12.15 lbs. (5.51 kg.).
- Shipping weight (approx.): 13.45 lbs. (6.1 kg.).

Features:

- Sixteen (16) power LEDs.
- Illuminated master power disconnect circuit breaker with manual reset.
- IEC 320 - 3-wire grounded line cord (detachable).
- Removable terminal blocks with locking screw flange.

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-04, Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions (H x W x D) (approximate):
1.625" (41.275mm) x 19.125" (486mm) x 8.5" (216mm)

