

### **Overview**



VertiLine16i

**VERTILINE™**

Altronix Vertiline16i CCTV Isolated Rack Mount Power Supply provides 16 fuse protected power outputs in a space saving 1U EIA 19" rack mount chassis which may be rack, wall or shelf mounted. This unit features individually selectable 24VAC and/or 28VAC power outputs with surge suppression. Vertiline CCTV Isolated Rack Mount Power Supplies are also available in eight (8) output models.

### **Specifications**

***Input:***

- Selectable 115VAC 60 Hz/230VAC 50/60 Hz input.
  - 115VAC 60 Hz., 7 amp.
  - 230VAC 50/60 Hz., 4 amp.

***Output:***

- Sixteen (16) individually selectable 24VAC or 28VAC power outputs with OFF position.
- 24VAC or 28VAC @ 16 amp max. total (1 amp per device, 3 amp max.).
- Individual electronically isolated outputs.
- Sixteen (16) external blade fuse protected outputs rated @ 3 amp.
- Surge suppression.

***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- 146-170 BTU/Hr.

***Electrical (cont'd):***

- System AC input VA requirement:  
115VAC: 805VA, 230VAC: 920VA.

***Mechanical:***

- Units can be rack, wall or shelf mounted.
- Modular 1U standard EIA 19" rack mount chassis
- Enclosure Dimensions (H x W x D approx.):  
1.625" (41.275mm) x 19.125" (486mm) x 8.5" (216mm)
- Product weight (approx.): 12.15 lbs. (5.51 kg.).
- Shipping weight (approx.): 13.45 lbs. (6.1 kg.).

***Features:***

- Sixteen (16) power LEDs.
- Illuminated master power disconnect circuit breaker with manual reset.
- IEC 320 - 3-wire grounded line cord (detachable).
- Removable terminal blocks with locking screw flange.

### **Agency Approvals**



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-04, Audio, Video and Similar Equipment.



European Conformity

***Enclosure Dimensions (H x W x D) (approximate):***  
1.625" (41.275mm) x 19.125" (486mm) x 8.5" (216mm)

