



Features

- 1/3 inch Sony Super HAD CCD
- High Resolution : 550 TV Lines
- Built-in DC Iris Vari-focal Lens(f=4~9mm)
- Auto White Balance
- AGC, BLC, Flickerless (On/Off)
- Min Illumination : 0.3Lux
- Extra Video Out Port for Installer
- 3-Axis Camera Construction
- Vandal-proof Dome Housing
- Diameter of Bubble : 100mm
- Heater Optional




ACCESSORY

- CNB-WVB100 : Wall Mount Bracket for Vandal Proof Dome Camera



DIMENSIONS



SPECIFICATIONS

Model	V1310NVD	V1310PVD
Signal System	NTSC	PAL
Scanning System	2:1 Interlace	
Sync. System	Internal	
Image Sensor	1/3 Inch SONY Super HAD CCD	
Total / Effective Pixels	410K/380K	470K/440K
Horizontal Resolution	550 TV Lines	
Video Output	Composite: 1.0V p-p, 75Ω, Unbalanced	
S/N Ratio	More than 50dB (AGC Off)	
Lens	DC Iris Vari-focal Lens (f=4~9mm)	
Min.Illumination	0.3 Lux	
White Balance	Auto	
AGC/BLC/Flickerless	On/Off (Dip Switch)	
Shutter Speed	1/60~1/100,000 sec	1/50~1/100,000sec.
Supplied Voltage	DC 9V~ 15V (Recommendation DC12±0.5V)	
Power consumption	Max. 3W / 250mA	
Heater (Option)	Operation Temperature : Under 10℃	
Dimensions(ØxH)	100.0 x 101.0 mm	
Weight	Approx. 844g	