

Features:

- Weatherproof bullet camera construction ideal for indoor/outdoor applications
- Unique removable sunshade housing protects camera from weather elements
- Rubber 'O' ring prevents moisture from entering camera housing
- Ideal for wall, ceiling or table mounting with or without using sunshade housing
- Exceptional 380 lines of Resolution
- Super Low 0.3 Lux Sensitivity



Model: DCB100012

Weatherproof B&W Bullet Camera with Sunshade

Specifications

Image Sensor	1/3" Interline transfer type B&W CCD
Effective Pixels	510H x 492V (250K)
Scanning System	525 Lines 2:1 Interlace
Scanning Frequency	15.734KHz (H), 59.94Hz (V)
Resolution	380 TV-Lines
Shutter Speed	1/60 ~ 1/100,000 sec.
S/N Ratio	More than 48dB (AGC off)
Sync. System	Internal
Min. Illumination	0.3 LUX (F2.0)
Gain Control	Automatic
Video Output	1.0 Vp-p (75Ω load)
Lens	Fixed (3.6mm)
Viewing Angle	39 - 92 Degrees
Power Supply	DC12V ± 10%
Power Consumption	<100mA (DC12V)
Operating Temp	-10 to +45 C / 14 to 113F
Operating Humidity	90% RH Max.