



Major Features

<ul style="list-style-type: none"> 4 channel standalone security digital video recorder designed for vehicles on the move 	<ul style="list-style-type: none"> Hardware double Anti-Vibration & Anti-Shock
<ul style="list-style-type: none"> CCTV or VGA/LCD monitor outputs 	<ul style="list-style-type: none"> Data Archive with USB (Slave)
<ul style="list-style-type: none"> Support both 2.5" and 3.5" Hot-swappable HDD 	<ul style="list-style-type: none"> Software Video Stabilizer
<ul style="list-style-type: none"> Video compression: MPEG4 	<ul style="list-style-type: none"> Protection power circuit for peak voltage
<ul style="list-style-type: none"> Sensor/Motion trigger or continuous recording 	<ul style="list-style-type: none"> Stable power output for cameras
<ul style="list-style-type: none"> Auto-cooling system and capable of operating under a lower than usual standard operating voltage 	<ul style="list-style-type: none"> 7 segments LED for real time information

Performance


Product	EB1304 MOB
Video input	4 cameras (BNC, 1Vp-p/750hm)
Video Format	NTSC
Video output	TV or VGA
Audio input/output	1
Display Rate (NTSC)	120 fps
Recording Rate (NTSC)	D1: 15/5/1 (NTSC) CIF: 30/15/10/5/1 (NTSC)
Sensor Input	4
Relay Output	1
Backup	Removable HDD
Power Source	DC 12/24V

NOTE: All specifications subject to change without prior notice

Product Specification

- 4 composite video inputs (BNC connector)
- 1 Composite or 1 VGA outputs
- Video compression: MPEG4
- Video Format: NTSC
- 1 channel audio input/output
- Display Resolution:

- D1 mode: 720 x 480 (NTSC)
 - CIF mode: 360 x 240 (NTSC)
- ◆ Display frame rate:
- ◆ Total 120 fps (NTSC)
- ◆ Hue/Brightness/contrast/Saturation adjustable
- ◆ Recording frame rate
 - CIF mode: 120 fps (NTSC)
 - D1 mode: 60 fps (NTSC)
- ◆ Recording modes:
 - Schedule (00:00~24:00 set by hour)
 - Sensor/Motion/Continuous
- ◆ Auto recycle recording
- ◆ Auto record enabling
- ◆ Password authentication mechanism
- ◆ Setup: On screen display and 7 segment LED
- ◆ Operating Temperature: 5 – 55C (Fan will automatically operate when it's over 50C. HDD will automatically stop recording when it is over 60C)
- ◆ Operating Shock: 20G, 11ms
- ◆ Operating Vibration: 5 ~ 500Hz, 1G
- ◆ Playback
 - Instant access playback
- ◆ 4096 event lists supported
 - Video search by date/time/event (Alarm/motion/video loss)
 - Easy to playback and backup on windows 2000/XP via exclusive playback application
 - Output as AVI files (Support Windows Media Player)
 - Backup (Removable hard disk – hot swap)
 - Support Watermark function for image verification
- ◆ I/O
 - 4 sensor inputs and 1 relay output
 - Relay output controls alarm, lock, light, or other devices
- ◆ Dimension: (L) 258mm x (M) 200mm x (H) 80mm
- ◆ Weight: 2.5kg



AVerMedia®

423 Dixon Landing Road, Milpitas, CA 95035 USA

U.S: (Tel) 1-408-263-3828 (Fax) 1-408-263-8132

Homepage: www.avermedia-usa.com | Email: avtnvd@avermedia-usa.com