

## SPECIFICATIONS

Pickup device: 1/3" interline transfer CCD

Picture element: 510x492(EIA) 500x580(CCIR)

Horizontal resolution: 420 TV lines

Sensitivity: 0.04 lux/F=1.2

S/N ratio: Over 48 dB

Electronic shutter: Up to 1/100,000

Back light comp: On

AGC: On

Gamma correction: >0.45

Video output: 1.0Vp-p,75 ohm

Power source: 12VDC+/-10%,150mA

Sync.mode: Internal Sync.

Dimension: 150mm O.D.\*50mm H.

Operating temperature: -10°C to +50°C

## **ESD120**

## 1/3" B/W CCD Camera

A conventional smoke detector built with B/W CCD cameras for discreet surveillance. It comes standard with one B/W CCD camera that delivers a clear and sharp picture for side viewing; and it is easy to change different lenses to adopt the best view angles of the room. The ESD120 can simultaneously install up to four cameras for the most economic and effective way of security surveillance.

## **FEATURES**

- A conventional smoke detector built with a discreet camera for surveillance purposes.
- It can accommodate up to four cameras to effectively view 360 degrees of a room from one location.
- High sensitivity 0.04 lux/F=1.2 and fast electronic shutter allows the camera to be used in various light levels.
- Easily adjustable cameras and lenses for best view angles.
- Compact size for easy installation and operation.