



LTC 0355 Series Monochrome Cameras



- ▶ 1/3-inch format CCD imager
- ▶ High sensitivity
- ▶ Advanced digital signal processing
- ▶ High resolution
- ▶ Auto detection of lens type
- ▶ Easy to install
- ▶ Accepts AC or DC voltage

The LTC 0355 series are compact rugged, 1/3-inch image format digital high monochrome CCD cameras. Their superior sensitivity and high resolution provide optimal performance in virtually all environments. Easy Installation, digital signal processing, on screen displays, superior picture quality and reliability brings the video performance of high resolution monochrome cameras to a level never reached before. The LTC 0355 series is the best choice for first time and professional users.

The LTC 0355 cameras also comes with a lens wizard that automatically detects the type of lens installed and provides an OSD guide that allows the installer to easily adjust the lens level and focus without special tools or filters. The ability to operate on AC or DC provides added flexibility to system designs and reduces the amount of training and support items to keep on-hand. This fully automatic camera is ready to work for you, and is easy to install in even the most demanding applications. On-screen Displays (OSD) provide quick and easy access to all camera features.

embedded in the video signal of all Bosch Dinion cameras. With Bilinx technicians can check status, change camera settings and even update firmware from virtually anywhere along the video cable. Bilinx reduces service and installation time, provides for more accurate set-up and adjustment, and improves overall performance. In addition, Bilinx uses the standard video cable to transmit alarm and status messages, providing superior performance without additional installation steps.

Certifications and Approvals

Electromagnetic Compatibility

EMC Immunity: According EN50130-4

EMC Emission: According EN505022 class B

According FCC, class B part 15

Safety

LTC 0355/10 and LTC 0355/50: EN60065

LTC 0355/20 and LTC 0355/60: UL6500

Functions

Bilinx Technology

The LTC 0355 series cameras incorporate Bilinx. Bilinx is a bidirectional communication capability

Parts Included

Quantity	Components
1	LTC 0355 Series Monochrome Camera
1	Spare male 4-pin lens connector
	Lens not included

Technical Specifications

Electrical

Model No.	Rated Voltage	Voltage Range	System
LTC 0355/10	12 VDC 24 VAC 50Hz	10.8-39 VDC 12-28 VAC 45-65 Hz	CCIR
LTC 0355/20	12 VDC 24 VAC 60Hz	10.8-39 VDC 12-28 VAC 45-65 Hz	EIA
LTC 0355/50	230 VAC 50Hz	85-265 VAC 45-65 Hz	CCIR
LTC 0355/60	120 VAC 60Hz	85-265 VAC 45-65 Hz	EIA
Power Consumption	4 W, excluding lens		
Imager	Interline transfer CCD 1/3-inch image format		
Active Pixels			
CCIR Models:	752 H x 582 V		
EIA Models:	582 H x 494 V		
Sensitivity (3200 k)			
	Usable Picture (50 IRE)	Full Video	
Scene Illumination ¹⁾	0.09 lux (0.009 fc)	0.36 lux (0.036 fc)	
Imager Illumination	0.018 lux (0.0018 fc)	0.072 lux (0.0072 fc)	
Horizontal Resolution	570 TVL		
Signal-to-Noise Ratio	50 dB		
Gain	Auto, 21 dB (max)		
Electronic Shutter	Automatic, 1/50 to 1/500000 sec. (CCIR), 1/60 to 1/600000 sec. (EIA)		
Aperture Correction	Horizontal and vertical, symmetrical		
Backlight Compensation	Center window weighting		
Video Output	Composite video 1.0 Vpp, 75 ohm		
Synchronization			
Line-Lock	(When powered by AC only) Synchronizes the camera to the power line zero crossing for roll-free vertical interval switching. Vertical phase delay can be adjusted (0 - 358 degrees) to allow vertical synchronization in multi-phase power installations.		
Crystal-Lock	(When DC-supply or L/L off) Internal crystal reference is standard on all models.		
Controls			
	Video level		
	Shutter: AES / off / flickerless		
	AGC: on / off		
	BLC: on / off		
	Auto black: on / off		
	Vphase adjustment: 0 - 358 degrees		

1) For F/1.2, 89% scene reflectance.

Mechanical

Connectors	- Video output: BNC
	- Video / DC-IRIS connector: 4-pin EIA-J
Power	
LTC 0355/10 and LTC 0355/20:	push type connectors, polarity independent, isolated from video output terminals
LTC 0355/50:	2-wire power cord with Euro plug
LTC 0355/60:	2-wire power cord with polarized plug
TripodMount	Top and Bottom, 1/4-inch 20 UNC
LensMount	C and CS
Dimensions (HxWxD)	58 x 66 x 122 mm (2.28 x 2.6 x 4.8 inch) including connectors
Weight	0.45 kg (0.99 lb)

Environmental

OperatingTemperature	-20°C to 50°C (-4°F to 122°F)
StorageTemperature	-25°C to 70°C (-13°F to 158°F)
OperatingHumidity	5% to 93% non-condensing

Ordering Information

Model | Description

LTC 0355/10 Monochrome Camera
1/3-inch B/W CCIR, DSP, 570 TVL, 12 VDC/240 VAC, 50 Hz

LTC 0355/20 Monochrome Camera
1/3-inch B/W EIA, DSP, 570 TVL, 12 VDC/24 VAC, 60 Hz

LTC 0355/50 Monochrome Camera
1/3-inch B/W CCIR, DSP, 570 TVL, 230 VAC, 60 Hz

LTC 0355/60 Monochrome Camera
1/3-inch B/W EIA, DSP, 570 TVL, 120 VAC, 60 Hz

Hardware Accessories

LTC 3364/40 Varifocal Lens
1/3-inch, 2.8 – 12 mm, DC-iris, CS-mount F1.4-360, 4-pin

LTC 3374/20 Varifocal Lens
1/3-inch, 5 – 50 mm, DC-iris, CS-mount F1.4-185, 4-pin

TC 120PS Power Supply Unit
110-120 VAC/15 VDC, 50/60 Hz, 300mA

TC 220PS Power Supply Unit
230 VAC/15 VDC, 50 Hz, 10 VA

TC 220PSX-24 Power Supply Unit
230 VAC/20 VAC, 50 Hz, 20 VA

TC 1334 Power Supply Unit
120 VAC/24 VAC, 60 Hz, 30 VA

Americas:
Bosch Security Systems
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 585 223 4060
Fax: +1 800 289 0096
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 (0) 40 27 83955
Fax: +31 (0) 40 27 86668
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by