


Features Overview (BASIC, WEB, IT, SECURE)

					Basic Models	Web Models	IT Models	Secure Models
Software Features (All Models)								
Digital zoom (up to 8x, continuous) with panning	-	X	X	X				
Motion JPEG/MxPEG video streaming	X/X	X/X	X/X	X/X				
Custom exposure windows	X	X	X	X				
Video Motion detection	X	X	X	X				
Time and event control (FTP, email, logos)	X	X	X	X				
Custom time tables/holidays	-	X	X	X				
Web functionality (FTP, email)	X	X	X	X				
Quad/MultiView in browser	X	X	X	X				
Recording/Playback in browser	X	X	X	X				
Logo generator, animated	-	X	X	X				
Single image recording (pre-/post-alarm images)	3	3	10	50				
Terabyte ring buffer (Win/Lin/Mac) via network	-	-	X	X				
Continuous video/audio recording, 0.2 to 30 fps	-	-	X	X				
Video/audio recording (event-triggered)	-	-	X	X				
Event-controlled frame rate with continuous audio	-	-	X	X				
Flexible event logic	-	-	-	X				
Master/Slave arming by one camera	-	-	-	X				
Scheduled privacy zones, several areas	-	-	-	X				
Bidirectional audio (IP) from/to browser	-	-	X*	X*				
Customized voice messages	-	-	X	X				
VoIP telephony (Audio/Video, SIP)	-	-	X*	X*				
Alarm calls to softphones (SIP) e.g. X-Lite	-	-	X	X				
Remote alarm notification (via TCP/IP, IP Notify)	-	-	X	X				
RS232 Data Logger/Terminal	-	-	X**	X**				
Programming interface/HTTP API	-	-	X	X				
Security features (HTTPS/SSL, IP-level access control, network authentication IEEE 802.1X)	X	X	X	X				
Model Feature List								
Image size	VGA	3 Mega**	VGA	3 Mega**				
Image Sensor	Color	Color	Color/BW	Color/BW				
Standard lens for software version	L22*	L22*	L22*	L22*				
Audio support (Microphone/Speaker)	-/S*	-/S*	M/S*	M/S*				

The Web version is available only as M12 model

The Basic version is available only as D22 and Q22 model

The IT version is not available as Q22 model

*D22 IT and Secure models allow connecting an external speaker and microphone. D22 cameras do not have a microphone or speaker.



**3 MEGA resolution with 2048x1536 pixels; the B/W image sensors of the Sec-DNight versions have Mega resolution (1280x960 pixels)

**M22 models require the CamIO; not available for D22 models

*M12 models are delivered with the lenses specified by the customer