Color Bullet Cameras

NVCC-W27N

NVCC-W41N

Key Features

- 1/3" SONY SuperHAD CCD Sensor
- DSP (Digital Signal Processing)
- 380 or 480 TV Lines
- 0.1 Lux
- Sun-Shield w/ Bracket
- Weatherproof
- Compact Size

NUVICO®

NVCC-W27N

SPECIFICATIONS

Image Sensor	1/3" SONY SuperHAD CCD Sensor
Effective Pixel	512H X 492V
Scanning System	525 Lines, 2:1 Interlace
Scanning Frequency	15.734KHz (H), 59.94 KHz(V)
Resolution	380 TV Lines
Sutter Speed	1/60~1/100,000 sec
S/N Ratio	More than 48dB (AGC off)
Sync. System	Internal
Min. Illumination	0.1 Lux
White Balance	AWB
Video Output	VBS 1.0 Vp-p (75Ω Load)
Lens	3.6mm Fixed Lens
Power Supply	DC 12V (9V~14V), Regulated
Power Consumption	100mA (DC12V)
Operating Temp.	-10 °C ~ +50 °C
Dimension	40(W)mm x 103(D)mm

※ Must use regulated DC 12V power supply.

NVCC-W41N

SPECIFICATIONS

Image Sensor	1/3" SONY SuperHAD CCD Sensor
Effective Pixel	768H X 494V
Scanning System	525 Lines, 2:1 Interlace
Scanning Frequency	15.734KHz (H), 59.94 KHz(V)
Resolution	480 TV Lines
Sutter Speed	1/60~1/100,000 sec
S/N Ratio	More than 48dB (AGC off)
Sync. System	Internal
Min. Illumination	0.1 Lux
White Balance	AWB
Video Output	VBS 1.0 Vp-p (75Ω Load)
Lens	3.6mm Fixed Lens
Power Supply	DC 12V (9V~14V), Regulated
Power Consumption	100mA (DC12V)
Operating Temp.	-10 °C ~ +50 °C
Dimension	40(W)mm x 103(D)mm

※ Must use regulated DC 12V power supply.

NUVICO INC.
E-mail : sales@nuvico.com
www.nuvico.com
Toll Free: 866-523-1700, Tel: 201-541-1605
Fax: 201-541-1620

Distributed by: