



*Quality video over ordinary telephone wire...®*

## Model NV-208A-M Video Transceiver



### Features:



- Full-motion CCTV video at distances up to 750ft (225m) when used with any passive NVT transceiver or hub
- Up to 3,000ft (1 km) with an NVT active receiver or hub
- Male BNC allows connection directly to the camera or DVR
- Reliable Screwless UTP terminal connection
- Supports “up-the-coax” type control signal up to 750ft (225m)
- No power required
- Exceptional interference rejection
- Built-in transient protection
- Limited lifetime warranty

The NVT Model NV-208A-M Video Transceiver is a passive (non-amplified) device that allows the transmission of real-time monochrome or color video over Unshielded Twisted-Pair (UTP) telephone wire. Baseband (composite) signals of any type are supported.

An improvement over NVT's popular NV-213A video transceiver, the NV-208A-M features a Screwless UTP terminal block and Male BNC allowing connection directly to the camera or DVR. It is capable of delivering a fully equalized signal to the DVR when used with any Active NVT Receiver, yet is compatible with all of NVT's passive products for applications under 750ft (225m). The NV-208A-M Video Transceiver also incorporates new improved transient protection that eliminates the need for a ground screw.

The unparalleled interference rejection and low emissions of the NV-208A-M allow video signals to co-exist in the same wire bundle as telephone, datacom, or low-voltage power circuits. This allows the use of a shared or existing cable plant. As with all NVT products, the NV-208A-M carries a limited lifetime warranty and is UL and cUL listed and CE compliant.

### Network Video Technologies

4005 Bohannon Drive • Menlo Park, CA • 94025 • USA  
(+1) 650.462.8100 • 800.959.9870 • FAX (+1) 650.326.1940  
[www.nvt.com](http://www.nvt.com) • [info@nvt.com](mailto:info@nvt.com)



*Quality video over ordinary telephone wire...®*

# Model NV-208A-M Video Transceiver

## Technical Specifications

### Video

Frequency response	DC to 5 MHz
Attenuation	0.5 dB typ
Common-mode / Differential-mode rejection	
15 KHz to 5 MHz	60 dB typ
Impedance	
Coax, male BNC	75 ohms
UTP, Screwless terminal blocks	100 ohms

### Power

No external power required

### Environmental

Temperature	-20 to +75°C
Humidity (non-condensing)	0 to 95%
Transient Immunity	per ANSI / IEEE 587 C62.41

### Wire Type

Network Wiring	One Unshielded Twisted Pair
	24-16 AWG (0,5-1,31 mm)
Category Type	2 or better
Impedance	100 ± 20 ohms
DC Loop Resistance (24 AWG)	52 ohms per 1,000 ft (18 ohms per 100 m)
Differential Capacitance	19 pF/ft max (62 pF/m max)

### Mechanical

Body Length	1.7 inches (43mm)
Body Height	0.8 inches (21mm)
Body Width	0.6 inches (14,5mm)
Weight	1.1 oz (34 g)

Specifications subject to change without notice.

### Network Video Technologies

4005 Bohannon Drive • Menlo Park, CA • 94025 • USA  
(+1) 650.462.8100 • 800.959.9870 • FAX (+1) 650.326.1940  
[www.nvt.com](http://www.nvt.com) • [info@nvt.com](mailto:info@nvt.com)

Copyright © 2005 NVT, Inc.

411-208-1-A