

TLSP Corner Mount

SPEAKER/MICROPHONE

DESCRIPTION

The Model TLSP Corner Mount is a two-way talk/listen speaker/microphone with built-in electret condenser microphone and a 3" speaker. Vandal resistant housing is especially designed for mounting in a corner or between wall and ceiling. When part of a Louroe Audio System, TLSP Corner Mount provides listen and talkback capabilities between the remote area and the Louroe Base Station.

APPLICATION

- Correctional Facilities
- Transportation Terminals
- Juvenile Facilities
- Public Acces Areas
- Parking Structures
- Areas where vandalism is a concern

IMPORTANT NOTICE

When this equipment is used as part of an audio monitoring system, the law requires that the public be given notice of AUDIO MONITORING ON THE PREMISES. A decal notice is included with each microphone shipped.




Federal Law References:
Federal Regulations, US Code, Title 18. Crime and Criminal Procedure, Sec 2510.

WIRING REQUIREMENTS

- 4 Conductor consisting of (all in the same jacket):
- 2 Conductor shielded, 20 AWG with AWG 22 drain (microphone connection)
 - 2 Conductor unshielded, 18 AWG (speaker connection)
West Penn 356 or equivalent

NOTE: Unshielded cable is not recommended for microphone connections.



TLSP CORNER MOUNT

FEATURES

- Vandal resistant 18 gauge CRS housing
- Mounts in a corner or between wall and ceiling
- Face dimensions: 8 3/4 x 6"
- May be mounted up to 1,000 ft. from Louroe Base Station
- Phantom powered from the Louroe Base Station
- Microphone can pick up normal sounds 15' away or within a 30° dia. circle

SPECIFICATIONS (Microphone)

Type	Electret condenser
Output	Line Level (0 dB @ 1KΩ)
Output impedance (mic only)	600Ω unbalanced
Frequency response	40 Hz to 15 kHz ± 1 dB
Current drain	4 mA
Supply voltage	12 Vdc

SPECIFICATIONS (Speaker)

Power rating	2W
Input	70.7V constant
Frequency response	300 Hz to 4 kHz ± 1dB
Impedance	8Ω
Speaker size	3"
Weight (net)	3.0 Lbs (1.4 Kg)

MS-CR-3-TLSP-CM