

5 MP Fixed Outdoor Bullet Camera



- 24/7 Full Time Color
- 5 MP High Performance CMOS
- Up to 2560 x 1944 Resolution
- 2.8 mm Fixed Lens (-F28 Model)
- 3D DNR, OSD Menu
- Up to 65 ft (20 m) White Light Range
- 130 dB True WDR
- Multiprotocol Output:
TVI/AHD/CVI/CVBS
- Up-the-Coax (HIKVISION-C)
- IP67 Protection

WEC SCC75B2/28U Fixed Bullet Outdoor Camera features an $f/1.0$ lens aperture for maximum light gathering capability to provide full color imaging in extremely dark settings.

The camera also contains a powerful auxiliary white light source to enhance colors and illuminate the scene when it approaches total darkness or on a defined schedule.

The 2.8 mm (-F28 model) and 3.6 mm (-F model) fixed lens options are optimized for viewing angles that fit any situation. 130 dB True WDR (Wide Dynamic Range) ensures that ideal images are captured regardless of the lighting conditions.

Available models:

SCC75B2/28U: 2.8 mm fixed lens



Specifications

SCC75B2/28U	
Camera	
Image Sensor	5 MP progressive scan CMOS
Signal System	NTSC
Resolution	2560 (H) × 1944 (V)
Frame Rate	TVI: 5 MP @ 20 fps, 4 MP @ 30 fps, 4 MP @ 25 fps, 1080p @ 30 fps, 1080p @ 25 fps CVI: 4 MP @ 30 fps, 4 MP @ 25 fps AHD: 5 MP @ 20 fps, 4 MP @ 30 fps, 4 MP @ 25 fps CVBS: NTSC
Minimum Illumination	Color: 0.0005 lux @ (f/1.0, AGC on), 0 lux with white light
Shutter Time	1/30 s to 1/50,000 s
Slow Shutter	Maximum 16x
Lens	2.8 mm fixed lens
Field of View	Horizontal FOV: 99.7°, vertical FOV: 72°, diagonal FOV: 139.8°
Lens Mount	M16
Strobe Light Alarm	Yes
Day/Night	Color
Angle Adjustment	Pan: 0° to 360°; tilt: 0° to 90°; rotate: 0° to 360°
WDR	130 dB
Menu	
White Light	Auto/off
Image Mode	STD/HIGH SAT
AGC	Yes
Day/Night Mode	Color
White Balance	Auto/manual
Auto Exposure Mode	WDR/BLC/HLC/Global/HLS/Anti-Banding
Privacy Mask	4 programmable privacy masks
Motion Detection	4 programmable areas
Noise Reduction	3D DNR
Language	English
Functions	Brightness, sharpness, mirror, smart light
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
General	
Operating Conditions	-40° F to 140° F (-40° C to 60° C), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ± 25% <i>* The use of one power adapter per camera is recommended.</i>
Power Consumption	Maximum 3.5 W
Protection Level	IP67
Material	Metal
White Light Range	Up to 65 ft (20 m)
Communication	Up-the-Coax, protocol: HIKVISION-C (TVI output)
Dimensions	2.68" x 2.76" x 6.62" (68 mm x 70 mm x 168.2 mm)
Weight	Approximately 0.77 lbs (350 g)

Accessories (not included)



Dimensions

