

VERSITON


VIDEO TECHNOLOGY

Lite IP Series

VIC-40EM2

VIC-40EM3

4MP Network IR Water-Proof Dome Camera



2.8MM
VIC-40EM2
3.6MM
VIC-40EM3


4MP

TRUE WDR

Features

- 4MP (2592 × 1520) H.265 full real time coding
- Max.re solution:
- ICR auto switch, true day / night
- 10 ~ 20m IR night view distance
- Third generation of dot matrix LED IR lights, small size, efficient heat dissipation, long lifespan
- 3D DNR, physical WDR
- Support HLC, BLC and defogging
- ROI coding
- Support CVBS video output and one-way audio
- PoE power supply optional
- Support smart phone, iPad, remote monitoring
- Support P2P
- P66 ingress protection
- Support three streams

Dimensions



Available Accessories



Specifications

Specifications	Model	VIC-40EM2 / VIC-40EM3
Camera		
Image Sensor		1 / 3 "CMOS
Image Size		2688 × 1520
Electronic Shutter		1 / 25 s ~ 1 / 100000 s
Auto Iris		Fixed iris
Min. Illumination		0.05 lux @F1.2, AGC ON; 0 lux with IR
Lens		3.6 mm @F1.6, angle of view : 72° : VIC-40EM3 2.8 mm : VIC-40EM2
Lens Mount		M12
Day & Night		ICR
Wide Dynamic Range		120dB
BLC		Yes
HLC		Yes
Defogging		Yes
Digital NR		2D / 3D DNR
Angle Adjustment		Any angle
Image		
Video Compression		H.265 / H.264 / MJPEG
H.265 Compression Standard		Main Profile @Leve4,1 High Tier
Resolution		4MP (2592 × 1520), 2K (2560 × 1440), 3MP (2304 × 1296), 1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480 × 240
Main Stream		60Hz : 4MP(1 ~ 30fps) / 2K(1 ~ 30fps) / 3MP(1 ~ 30fps) / 1080P(1 ~ 30fps) / 720P(1 ~ 30fps) 50Hz : 4MP(1 ~ 25fps) / 2K(1 ~ 25fps) / 3MP(1 ~ 25fps) / 1080P(1 ~ 25fps) / 720P(1 ~ 25fps)
Bit Rate		64 Kbps ~ 10 Mbps
Encode Mode		VBR / CBR
Quality		Five levels under VBR; Freely adjustable under CBR
Image Settings		ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. adjustable through client software or web browser
Audio Compression		G711A / U
ROI		Each ROI to be configured separately
Interfaces		
Network		RJ45
Video Output		CVBS video output (BNC × 1)
Audio		MIC IN × 1
Functions		
Remote Monitoring		IE browsing, CMS remote control
Online Connection		Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol		TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Interface Protocol		ONVIF, GB-T/28181-2011
Storage		Network remote storage
Smart Alarm		Motion alarm
PoE		Optional
IR Distance		10 ~ 20m
Water-proof		IP66
Others		
Power Supply		DC12V (PoE power supply optional)
Power Consumption		< 2.5W
IR Consumption ON		< 5W
Operating Environment		- 20 °C ~ 50 °C, 10 % ~ 90 % humidity
Dimensions (mm)		Φ 87 × 108
Weight (net)		427g
Installation		Pendent mounting (Wall mounting available with the junction box and bracket

Designs and specifications are subject to change without notice.

Tel: 562-428-0010 Fax: 562-513-1004 E-mail: sales@versiton.com | 10811 Shoemaker Ave., Santa Fe Springs, CA 90670 VERSITON VIDEO TECHNOLOGY.