

SV-HDW7120

2.0Megapixel 1080P HDCVI PIR Style Hidden Camera



Features

- 1/2.8" 2.0Megapixel CMOS
- 25/30fps@1080P, 25/30/50/60fps@720P
- High speed, long distance real-time transmission
- HD definition
- OSD Menu, DVR control as default, coaxial control optional
- Day/Night (ICR), AWB, AGC, BLC, 2D-DNR
- 3.7mm pinhole lens
- DC12V

SV-HDW7120

Technical Specifications

| | |
|------------------------|--|
| Model | SV-HDW7120 |
| Camera | |
| Image Sensor | 1/2.8" 2Megapixel CMOS |
| Effective Pixels | 1920(H)×1080(V) |
| Electronic Shutter | 1/60s~1/60,000s |
| Video Frame Rate | 25/30fps@1080P, 25/30/50/60fps@720P |
| Synchronization | Internal |
| Min. Illumination | 0.01Lux@F1.2(AGC ON) |
| Video Output | 1-channel BNC HDCVI high definition video output/ CVBS 960H definition video output (Can switch) |
| Camera Features | |
| Max. IR LEDs Length | N/A |
| Day/Night | Auto / Color / B/W |
| Noise Reduction | 2D |
| OSD Menu | Support |
| Lens | |
| Focal Length | 3.7mm pinhole lens |
| General | |
| Power Supply | DC12V±10% |
| Power Consumption | Max 8W |
| Working Environment | -20°C~+60°C / Less than 95%RH (no condensation) |
| Transmission Distance | Over 500m via 75-3 coaxial cable |
| Ingress Protection | N/A |
| Dimensions | Φ120mm×60mm |
| Weight | 0.18kg |

Dimensions (mm)

