

Network Keyboard



- Control High Speed Domes, DVRs and Network Video Servers
- Three-dimensional Joystick Control for PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour and Pattern Control
- Support for Auxiliary Functions
- On-screen Menu
- Supports SmartPSS (via USB connection)

Technical Specification

System

Keyboard Key Panel	Electromechanical
Joystick	Three-axis Vector-solving Twisting Function Return to Center
Display	LCD, 75.20 mm x 33.85 mm (2.96 in. x 1.33 in.)

Interface

Keyboard Connector	RJ45 RS232 RS485 RS422 USB
Keyboard Communication	Direct Mode, Network Mode
Direct Mode	Interface: RS232/RS485 DVR Protocol: DH2 PTZ Protocol: DH-SD/Pelco-D/Pelco-P/Pelco-D1/Pelco-P1
Network Mode	Interface: RJ45 DVR/Network PTZ: IP Address/Port/Protocol

Electrical

Power Supply	Power Adapter Input: 100 VAC to 240 VAC, 50/60 Hz Output: 12 VDC, 1000 mA
Power Consumption	5 W

Environmental

Operating Temperature	-10° C to +55° C (14° F to +131° F), 95% RH
Operating Humidity	10% to 90%
Atmospheric Pressure	86 kpa to 106 kpa

Construction

Dimensions	330.0 mm x 160.0 mm x 37.50 mm (12.99 in. x 6.30 in. x 1.48 in.) Height with Joystick: 100 mm (3.94 in.)
Net Weight	2.50 kg (5.52 lb)