

ED9732(64)H5NV-2



32/64CH CLEAR 4K NETWORK VIDEO RECORDER

Specification:

Model	ED9732H5NV-2	ED9764H5NV-2
System	Compression	Standard H.265
	OS	Embedded Linux
Video	Network Input	32 CH IPC input
	Network Access Bandwidth	256Mbps
	Network Access Format	64 CH IPC input
	Output	320Mbps
Audio	Network Input	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P@25 / 30fps
	2-way Audio	HDMI × 2 : one of 4K × 2K / 1920 × 1080 / 1280 × 1024 the other of 1920 × 1080 / 1280 × 1024 VGA × 1 : 1920 × 1080 / 1280 × 1024
Record	Record Stream	32 CH IPC audio input
	Resolution	64 CH IPC audio input
Playback	Mode	RCA × 1
	Simultaneous Playback	RCA × 1
	Search	Dual stream recording
	Smart Search	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P
Alarm	Function	Manual, timer, motion, sensor
	Mode	Max 16 CH
	Input	Time slice / time / event / tag search
	Output	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
Network	Triggering	Play, pause, FF, FB, digital zoom, etc.
	Interface	Manual, sensor, motion, exception
Mobile Device	Protocol	8 CH local alarm input, support IPC alarm input
	Web Client	4 CH
Storage	OS	Record, snap, preset, e-mail, etc.
	HDD	RJ45 10 / 100 / 1000 Mbps × 2
Backup	Local Backup	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
	Network Backup	Max 10 users online
Port	USB	iOS, Android
	Remote Controller	Yes
Others	Power Supply	ATX
	Consumption	≤ 15W (without HDD)
	Dimensions (mm)	≤ 15W (without HDD)
	Work Environment	430 × 453 × 89 (W × D × H)

Main Feature:

- Support 32/64 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse
- Multi-mode recording: manual / timer / motion / sensor Playback : 16 CH simultaneously playback
- Search: time slice, time, event (manual, sensor, motion), tag search Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol, IE browse and CMS supported Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device Multi-user online simultaneously
- Authorization management, log review and device status review
- 4K output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises. Support NAT function and QRCode scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Android OS

Physical Interfaces:

