


ES1005KI USB Keyboard



Typical Application



Specifications

Model	ES1005KI
Compatible System	Window XP/7/8/8.1
Interface Type	USB 2.0, DirectX
Control	Joystick (3-axis control, rotating zoom)
Dimensions	167*177.5*116(mm)
Operating Temperature	-10 °C ~+55 °C
Operating Humidity	10% ~ 90% (Non-condensing)
Power Supply	5V DC via USB
Consumption	≤ 5W

Overview

ES1005KI is a USB keyboard independently developed by Hikvision and it can be accessed directly by the client software, platform software of iVMS series, DVR and PC-DVR, and can realize functions such as windows switching, PTZ control, picture capture, recording and etc..

ES1005KI is compatible with the USB joystick via USB HID protocol, and can access to the third-party platform software. It provides amply programmable buttons for setting custom function and has the advantage of simple interface and easy operation. The product can be widely applied in fields such as finance, transportation, telecommunication, education, water conservancy, and public security and so on.

Available Models

ES1005KI

Key Features

Power supply and communication by USB port directly.

3D PTZ control and 2 joystick control buttons.

Up to 15 programmable buttons are available.

Support digital tube to display the input content.

Support indicators to show the operation status of keyboard. Compatible with a various kinds of client software and platform software.

Support USB HID protocol.