

SNA Terminal Blocks T&B Catalog Number:

011527122

UPC Number: 66201995645 **Status:** Active

Description:

Gray, feed through terminal block with 6 mm spacing, 20 Amp rated UL current with screw clamp connection that accepts 22-12 AWG UL wire range

range	
Features	
	Double deck
	Self-locking clamp design prevents screw loosening Funneled side entry for up to two ferruled or non-
	ferruled solid or stranded wires
	Touch-safe IP20 protection
	High quality steel offers a very high over-torque resistance
	Compensates for the flattening of copper under contact pressure
	Clamp is protected from harsh environments by a zinc bichromate surface treatment
Application	
- I-laneauen	
	For use with applications ranging from standard distribution and control panels, to specialized applications in key industries such as traction, energy, maritime, explosive atmospheres, material handling, etc.
General	
Style	Double Deck Feed Through
Color	Gray
Mounting	DIN 1-3
Series	M 4/6.D2
Connection Technology	Screw Clamp
UL Wire Range (AWG)	22-12
Rated IEC Wire Range (Solid) (mm2)	4
Rated CSA Wire Size (AWG)	12
Dimension Information	
L x W x H (mm)	65.5 x 6 x 64.5
Spacing (mm)	6
L x W x H (in)	2.57 x 0.238 x 2.34
Spacing (inches)	0.236
Specifications	
UL Current (Amps)	20
UL Voltage (VAC)	600
Rated UL Wire Size (AWG)	12
IEC Voltage (VAC)	800
IEC Current (Amps)	32
CSA Voltage (VAC)	300
CSA Current (Amps)	25
Packaging	
i acitaging	
T&B Order Multiple	50
T&B Inner Pack	50



Package in Units	1000
T&B Sold in UOM	Each
T&B Weight Per UOM	3.5 lbs. per 100
Certifications	
Approvals	UL, IEC, CSA

For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321

Email:techsupport@tnb.com